

Camera G5 Bullet



Mechanical

Dimensions	Without mount: Ø75.5 x 74.4 mm (Ø2.97 x 2.93") With wall mount: Ø75.5 x 150 mm (Ø2.97 x 5.9")
Weight	Without mount: 225 g (7.94 oz) With wall mount: 315 g (11.11 oz)
Enclosure materials	Polycarbonate, aluminum alloy
Mount materials	Wall mount: aluminum alloy, polycarbonate Pole mount: aluminum alloy
Weatherproofing	IPX4
Resistance	IK04

Optics

Sensor	5 MP CMOS sensor
Lens	Fixed focal length
View angle	H: 84.4°, V: 45.4°, D: 99.8°
Night mode	Built-in IR LED illumination and IR cut filter

Video

Video compression	H.264, MJPEG
Resolution	2688 x 1512 (16:9)
Max. frame rate	30 FPS
Image settings	Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay

System

Processor specs	Dual-core Arm® Cortex®-A7 based chip
Networking interface	10/100 MbE RJ45
Max. power consumption	4W
Power method	PoE
Supported voltage range	37–57V DC
Button	Factory reset
Mounting	Wall, pole mount and ceiling
Operating temperature	-20 to 40° C (-4 to 104° F)
Operating humidity	0 to 90% noncondensing
Certifications	FCC, IC, CE

Audio

Microphone	Yes (Can be disabled in software)
------------	-----------------------------------



Software

UniFi OS application	UniFi Protect
Mobile app	UniFi Protect iOS™ and Android™



Specifications are subject to change. Ubiquiti products are sold with a limited warranty described at www.ui.com/support/warranty

©2022 Ubiquiti Inc. All rights reserved. Ubiquiti, the Ubiquiti U logo, UniFi Protect, and UniFi are trademarks or registered trademarks of Ubiquiti Inc. in the United States and in other countries. Android is a trademark of Google LLC. Arm and Cortex are registered trademarks of Arm Limited (or its subsidiaries) in the US and/or elsewhere. All other trademarks are the property of their respective owners.