

AXIS T8606 Media Converter Switch 24 V DC

AXIS T8606 Media Converter Switch 24 V DC allows connection to the network using standard Ethernet or ber optic cables that help lower the cost of installing the cameras over long distances. Perfect for city surveillance, airports and other long distance installations, AXIS T8606 is a DIN-mounted device that can convert an Ethernet signal to be used over optical ber cable. Surveillance integrators in the eld can also connect installation monitors and laptops (via the RJ45 connectors) to AXIS T8606 for camera maintenance and control. The media converter switch can be connected in a daisy chain network.

> 24 V DC IN

- > Convert Ethernet to optical fiber
- > Support for 10/100 Mbps
- > Two SFP slots and two RJ45 ports
- > Compatible with Axis network products



www.axis.com

General Supported products	All Axis network video products	Approvals	EN EN
Casing	Metal Color: White NCS S 1002-B		ICI KN Sa
Power	24 V DC, max 3.5 W (power supply not included)		IEC
Connectors	2x RJ45 connectors (10/100 Mbps) (Use shielded cables (STP)	Dimensions	15
	CAT5 or higher.) 2x SFP connectors (100/1000 Mbps) for SFP ber optic modules	Weight	28
	or SFP to copper modules 1x power	Included accessories	Bra
Display and indicators	Power LED indicator Network LED indicator (4x)	Warranty	Ax
Compliance	RoHS, REACH, WEEE, CE, EN 50022, IEC 60715, AS 2756	Environmental responsi	
Mounting	DIN Rail mount	www.axis.com/er	nvironr
Environment	Indoor/Cabinet		
Operating conditions	-40 °C to 75 °C (-40 °F to 167 °F) Humidity 10-85% RH (non-condensing)		
Storage conditions	-40 °C to 75 °C (-40 °F to 167 °F) Humidity 10-85% RH (non-condensing)		

Approvals	EMC EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32, KCC KN32 Class A, KN35 Safety IEC/EN 60950-1	
Dimensions	150 x 100 x 30 mm (5 15/16 x 3 15/16 x 1 3/16 in)	
Weight	284 g (0.63 lb)	
Included accessories	Bracket Mount DIN Clip, Installation Guide	
Warranty	Axis 3-year warranty, see www.axis.com/warranty	

sibility:

nmental-responsibility

1652658/EN/M1.4/012017

