

EB-685W

DATASHEET



Innovative teaching solution with a large scalable screen size of up to 100 inches to display HD-ready WXGA content for enhanced learning.

The EB-685W's ultra-short-throw design allows you to present large images from a very short distance with minimised shadows and glare. With a brightness level of 3,500 lumens, an HD-ready WXGA resolution, a 14,000:1 contrast ratio, and HDMI input, students benefit from sharp, clear images.

High-quality, bright images

Epson's 3LCD technology ensures high-quality images with equally high White and Colour Light Output for vivid colours and bright images, even in daylight, and three times brighter colours than leading competitive projectors¹.

Keep costs down

Project for longer with improved reliability and a longer lamp life of up to 10,000 hours in eco mode.

Enhanced learning

Split-screen functionality allows two pieces of content to be displayed simultaneously without compromising on quality. The moderator function allows teachers to remain in control, choosing what content to display.

Optional wireless capability

Wirelessly display content easily from a range of smart devices and Google Chromebooks using our iProjection App².

Document camera compatibility

Connecting the optional Epson document camera allows you to easily display images and 3D objects with incredible detail for the whole class to see.

KEY FEATURES

- **Up to 100-inch display and outstanding quality**
HD-ready WXGA resolution with Epson 3LCD technology
- **Reliable**
Improved reliability and a longer lamp life
- **Wireless Connectivity (Optional)**
Allows content to be shown from a range of devices
- **Long lamp life**
Up to 10,000 hours in eco mode
- **Ultra short throw projection**
For maximum installation flexibility



EPSON[®]
EXCEED YOUR VISION

PRODUCT SPECIFICATIONS

TECHNOLOGY	
Projection System	3LCD Technology
LCD Panel	0.59 inch with D9
IMAGE	
Colour Light Output	3,500 lumen- 2,900 lumen (economy)
White Light Output	3,500 lumen - 2,900 lumen (economy) In accordance with ISO 21118:2012
Resolution	WXGA, 1280 x 800, 16:10
Contrast Ratio	14,000 : 1
Native Contrast	300 : 1
Lamp	250 W, 5,000 h durability, 10,000 h durability (economy mode), 9,000 h durability (economy mode)
Keystone Correction	Manual vertical: $\pm 3^\circ$, Manual horizontal $\pm 3^\circ$
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Projection Ratio	0.28:1
Zoom	Digital, Factor: 1 - 1.35
Image Size	60 inches - 100 inches
Projection Distance Wide	0.4 m (60 inch screen)
Projection Distance Tele	0.6 m (100 inch screen)
Projection Lens F Number	1.6
Focal Distance	3.76 mm
Focus	Manual
Offset	6 : 1
CONNECTIVITY	
USB Display Function	3 in 1: Image / Mouse / Sound
Interfaces	USB 2.0 Type A, USB 2.0 Type B, RS-232C, HDMI in (3x), Composite in, RGB in (2x), RGB out, Stereo mini jack audio out, Stereo mini jack audio in (3x), Microphone input, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11b/g/n (optional), VGA in (2x), VGA out, MHL
Epson iProjection App	Ad-Hoc / Infrastructure
OTHER	
Warranty	36 months On site service or 8,000 h, Lamp: 12 months or 1,000 h Optional warranty extension available

LOGISTICS INFORMATION

SKU	V11H744041
EAN code	8715946605227
Country of Origin	Philippines

For more information please contact:

Telephone: 01952 607111 (UK)+
01 436 7742 (Republic of Ireland)
E-mail: enquiries@epson.co.uk
Chat: etalk.epson-europe.com
Fax: 0871 222 6740
+ Local call rate.

Web: www.epson.co.uk
www.epson.ie

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

EB-685W

WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- CD Manual
- Quick Start Guide
- USB cable
- Wall mounting bracket
- Warranty card

OPTIONAL ACCESSORIES

- Active Speakers (2 x 15W) - ELPSP02
V12H467040DA
- Control and Connection Box - ELPCB02
V12H614040DA
- Lamp - ELP91 - EB-68x/69x (250W)
V13H010L91
- Wireless LAN Adapter - ELPAP10
V12H731P01
- Table Mount for Ultra-short-throw Series - ELPMB29
V12H516040
- Ceiling Mount (White) - ELPMB23
V12H003B23
- Ceiling Pipe (450mm) - ELPFP13
V12H003P13
- Ceiling Pipe (700mm) - ELPFP14
V12H003P14

1. - Colour Brightness (Colour Light Output) measured in accordance with IDMS 15.4. Colour Brightness will vary depending on usage conditions. Leading Epson 3LCD business and education projectors compared to leading one-chip DLP projectors, based on NPD data for June 2013 through May 2014 and PMA Research data for Q1 through Q3 2013. For more information please visit www.epson.eu/CLO
2. -iProjection App available on Android and iOS devices, and Google Chromebooks.

EPSON[®]