



PE-304/604/BU/WU

Pendant speaker



Ultra lightweight for
high-ceiling venues.

PE-304/604/BU/WU

Pendant speaker

These pendant speakers are ABS resin bass-reflex enclosure with a 12 cm (5") cone-type woofer and a balanced-dome tweeter. They are intended to be installed suspended from a ceiling – they are very lightweight, with a stylish design inspired by modern lighting fixtures, allowing them to harmoniously blend in with a room design.

- Remarkably lightweight with stylish design inspired by modern lighting fixtures
- Ideally suited for BGM & announcements
- 8 Ω and 25V/70V/100V operation
- Input impedance is easily changed with a rotary switch on the top of the speaker
- With speaker cable, GRIPPLE® hanging wire & safety wire pre-attached, for faster, easier and more secure installation

Application examples



Airports



Factories




Shopping malls



Office buildings

Specifications



	PE-304BU/304WU	PE-604BU/604WU
Enclosure		Bass-reflex type
Rated Input	30W (100V, 70V line, 8 Ω), 3.7W (25V line)	60W (100V, 70V line, 8 Ω), 7.5W (25V line)
Rated Impedance	100V line: 330 Ω (30W), 1k Ω (10W), 3.3k Ω (3W), 10k Ω (1.3W) 70V line: 170 Ω (30W), 330 Ω (15W), 1k Ω (5W), 3.3k Ω (1.5W), 10k Ω (0.6W) 25V line: 170 Ω (3.7W), 330 Ω (1.9W), 1k Ω (0.6W), 3.3k Ω (0.2W), 10k Ω (0.1W) Low impedance: 8 Ω	100V line: 170 Ω (60W), 330 Ω (30W), 670 Ω (15W), 3.3k Ω (3W) 70V line: 83 Ω (60W), 170 Ω (30W), 330 Ω (15W), 670 Ω (7.5W), 3.3k Ω (1.5W) 25V line: 83 Ω (7.5W), 170 Ω (3.7W), 330 Ω (1.9W), 670 Ω (0.9W), 3.3k Ω (0.2W) Low impedance: 8 Ω
Sensitivity (1W, 1m)	90dB (330 Hz – 3.3kHz, pink noise)	
Frequency Response	95 Hz – 20kHz (–10dB)	110Hz – 20kHz (–10dB)
Speaker Component	12 cm (5") cone-type + balanced-dome tweeter (coaxial)	
UL Code	UL1480 UUMW, ULC-S541	
Operating temperature	–10 °C to +50 °C	
Finish	PE-304BU: Enclosure: ABS resin, black Grille: Surface-treated steel plate mesh, black, paint PE-304WU: Enclosure: ABS resin, white (RAL 9010 equivalent) Grille: Surface-treated steel plate mesh, white (RAL 9010 equivalent), paint	PE-604BU: Enclosure: ABS resin, black Grille: Surface-treated steel plate mesh, black, paint PE-604WU: Enclosure: ABS resin, white (RAL 9010 equivalent) Grille: Surface-treated steel plate mesh, white (RAL 9010 equivalent), paint
Dimensions	ø186 x 275 (H) mm (ø7.32" x 10.83") (not including wires and cable)	
Weight	2 kg (not including wires and cable)	2.9kg (not including wires and cable)
Accessory	GRIPPLE® No. 1 x 1, GRIPPLE® No. 2 x 1, Release key (for GRIPPLE®) x 1, Safety wire (ø1.5mm (ø0.06")) x 1, Hanging wire (ø2mm (ø0.08")) x 1, Speaker Cable (4-core FPL listed cable 4.6m (15.09ft) x 1	

*GRIPPLE® No. 1 and GRIPPLE® No. 2 are hangers for suspending the speaker. GRIPPLE® is a registered trademark of Gripple Limited, England.