



USB-C to DisplayPort Adapter Cable

Converts a DP Alt Mode Signal to a DisplayPort 4K Output, 2 m (6 ft.), Black
Part No.: [152464](#)

Easily convert a USB-based audio/video signal into DisplayPort format.

The Manhattan USB-C to DisplayPort Adapter Cable transmits a USB audio/video signal to a DisplayPort projector, flat-panel display, television or similar device. Built-in circuitry allows digital media enthusiasts to easily enjoy USB-based multimedia content on an Ultra High Definition (UHD) display or TV while maintaining simultaneous A/V reception at the source. Its UHD capability supports up to 3840x2160@60Hz and 4K to serve a wide range of resolutions in many devices and UHD applications including training, retail and trade show settings. Your source device must support DP Alt Mode. No additional setup is required. It effortlessly delivers digital content that is stored on a smartphone, tablet, Ultrabook or notebook computer to a display with DisplayPort input capabilities.

Features:

- Easily connects a USB-C DP Alt Mode device to a DisplayPort display, monitor or projector
- Delivers a clear, sharp resolution up to 3840x2160@60Hz; supports 4K Ultra HD video aspect ratio of 21:9
- Ideal for connecting a DisplayPort display to a DP Alt Mode-capable smartphone, tablet, Ultrabook, laptop and more
- Compatible only with a USB-C device that supports DP Alt mode; Thunderbolt 3 port compatible
- Slim design makes for a clutter-free desktop; direct-connect cable makes it the perfect travel companion
- Also available in 1 m (3 ft.) length [search part number 152471 at www.manhattanproducts.com]
- Bus powered: no external power supply needed
- Three-year warranty

Specifications:

Standards and Certifications

- CE
- FCC
- RoHS2
- USB 3.1
- HDCP
- DP Alt Mode

General

- Supports lane data rates of 5.4 Gbps (HBR2), 2.7 Gbps High Bit Rate (HBR) and 1.62 Gbps Reduce Bit Rate (RBR)
- Resolution: up to 3840x2160@60Hz
- Audio and video output through DP
- Bus powered: no external power supply
- Supports HDCP pass-through

Connections

- Input: USB 3.1 type-C male
- Output: DisplayPort male

Physical

- Adapter cable: 2 m (6 ft.)
- Weight: 0.1 kg (3.9 oz.)

Operating Environment

- Operation Temperature: 0 – 40°C (32 – 104°F)
- Storage Temperature: -20 – 60°C (-4 – 140°F)
- Humidity (noncondensing): 0 – 96%

System Requirements

- DP Alt Mode-supported device

Package Contents

- USB-C to DisplayPort Adapter Cable

