



3.5 HDD DATA SHEET

The Power of Agility for Home, SOHO, and SMB NAS Enclosures



IronWolf™ is designed for everything NAS. Get used to tough, ready, and scalable 24x7 performance that can handle multi-drive environments across a wide range of capacities.



Best-Fit Applications

- 1- to 8-bay network attached storage (NAS)
- Desktop RAID and servers
- Multimedia server storage
- Private cloud



Key Advantages

Optimised for NAS with AgileArray.™ AgileArray enables dual-plane balancing and RAID optimisation in multi-bay environments, with the most advanced power management possible.

Actively protect your NAS with IronWolf Health Management focusing on prevention, intervention, and recovery.¹

High performance means no lag time or downtime for users during workload traffic for the NAS. Seagate leads the competition with the highest-performing NAS drive portfolio.²

Rotational Vibration (RV) sensors. First in its class of drives to include RV sensors to maintain high performance in multi-drive NAS enclosures.³

Range of capacities up to 14 TB. More capacity options means more choices that will fit within the budget. Seagate provides a scalable solution for any NAS use-case scenario.

Do more in multi-user environments. IronWolf provides a workload rate of 180 TB/year. Multiple users can confidently upload and download data to the NAS server, knowing IronWolf can handle the workload, whether you are a creative professional or a small business.

Designed for always-on, always-accessible 24x7 performance. Access data on your NAS any time, remotely or on site.

1 M hours MTBF, 3-year limited warranty represents an improved total cost of ownership (TCO) over desktop drives with reduced maintenance costs.

¹ Contact your Seagate sales representative for further information.

² Performance may vary depending on user's hardware configuration and operating system.

³ Included on 4, 6, 8, 10, 12, and 14 TB models.



| Specifications | 14TB | 12TB | 10TB | 8TB | 6TB |
|---|--------------------|--------------------|--------------------|--------------------|--------------------|
| Standard Model Numbers | ST14000VN0008 | ST12000VN0008 | ST10000VN0008 | ST8000VN0022 | ST6000VN0033 |
| Interface | SATA 6Gb/s | SATA 6Gb/s | SATA 6Gb/s | SATA 6Gb/s | SATA 6Gb/s |
| Features and Performance | | | | | |
| Drive Bays Supported | 1 – 8 Bays | 1 – 8 Bays | 1 – 8 Bays | 1 – 8 Bays | 1 – 8 Bays |
| Multi-User Technology | 180 TB/year | 180 TB/year | 180 TB/year | 180 TB/year | 180 TB/year |
| Rotational Vibration (RV) Sensor | Yes | Yes | Yes | Yes | Yes |
| Dual-Plane Balance | Yes | Yes | Yes | Yes | Yes |
| Error Recovery Control | Yes | Yes | Yes | Yes | Yes |
| Max. Sustained Transfer Rate OD (MB/s) | 210MB/s | 210MB/s | 210MB/s | 210MB/s | 210MB/s |
| Spindle Speed (RPM) | 7,200 | 7,200 | 7,200 | 7,200 | 7,200 |
| Cache (MB) | 256 | 256 | 256 | 256 | 256 |
| Reliability | | | | | |
| Load/Unload Cycles ¹ | 600,000 | 600,000 | 600,000 | 600,000 | 600,000 |
| Non-recoverable Read Errors Rate, Max | 1 per 10E15 | 1 per 10E15 | 1 per 10E15 | 1 per 10E15 | 1 per 10E15 |
| Power-on Hours | 8,760 | 8,760 | 8,760 | 8,760 | 8,760 |
| Workload Rate Limit (WRL) | 180 | 180 | 180 | 180 | 180 |
| Mean Time Between Failures (MTBF, hours) | 1,000,000 | 1,000,000 | 1,000,000 | 1,000,000 | 1,000,000 |
| Limited Warranty (years) | 3 | 3 | 3 | 3 | 3 |
| Power Management | | | | | |
| Startup Current, Typical (12V, A) | 1.8 | 1.8 | 1.8 | 1.8 | 1.8 |
| Average Operating Power (W) | 7.9 W | 7.8 W | 7.8 W | 8.8 W | 8.1 W |
| Idling Average (W) | 5.3 W | 5 W | 5 W | 7.6 W | 7.2 W |
| Standby Mode/Sleep Mode, Typical (W) | 0.8/0.8 | 0.8/0.8 | 0.8/0.8 | 0.6/0.6 | 0.6/0.6 |
| Voltage Tolerance, Inc. Noise (5 V) | ±5% | ±5% | ±5% | ±5% | ±5% |
| Voltage Tolerance, Inc. Noise (12 V) | ±10% | ±10% | ±10% | ±10% | ±10% |
| Environmental/Temperature | | | | | |
| Operating (ambient, min °C) | 5 | 5 | 5 | 5 | 5 |
| Operating (drive case, max °C) ² | 70 | 70 | 70 | 70 | 70 |
| Non-operating (ambient, min °C) | -40 | -40 | -40 | -40 | -40 |
| Non-operating (ambient max °C) | 70 | 70 | 70 | 70 | 70 |
| Halogen-free | Yes | Yes | Yes | Yes | Yes |
| Environmental/Shock | | | | | |
| Shock, Operating/Non-operating: 2 ms (max) | 70Gs/250Gs | 70Gs/250Gs | 70Gs/250Gs | 70Gs/250Gs | 70Gs/250Gs |
| Environmental/Acoustics | | | | | |
| Idle (typical) ³ | 1.8 bels | 1.8 bels | 1.8 bels | 2.7 bels | 2.7 bels |
| Seek (typical) | 2.8 bels | 2.8 bels | 2.8 bels | 2.8 bels | 2.8 bels |
| Physical | | | | | |
| Height (mm/in) | 26.11 mm/1.028 in | 26.11 mm/1.028 in | 26.11 mm/1.028 in | 26.11 mm/1.028 in | 26.11 mm/1.028 in |
| Width (mm/in, max) | 101.85 mm/4.01 in | 101.85 mm/4.01 in | 101.85 mm/4.01 in | 101.85 mm/4.01 in | 101.85 mm/4.01 in |
| Depth (mm/in, max) | 146.99 mm/5.787 in | 146.99 mm/5.787 in | 146.99 mm/5.787 in | 146.99 mm/5.787 in | 146.99 mm/5.787 in |
| Weight (g/lb, typical) | 690 g/1.521 lb | 690 g/1.521 lb | 690 g/1.521 lb | 780 g/1.72 lb | 705 g/1.55 lb |
| Carton Unit Quantity | 20 | 20 | 20 | 20 | 20 |
| Cartons per Pallet / Cartons per Layer | 40/8 | 40/8 | 40/8 | 40/8 | 40/8 |

¹ Load/unload tested to 600,000 cycles.

² Seagate does not recommend operating at sustained case temperatures above 60°C. Operating at higher temperatures will reduce useful life of the product.

³ Idle measured in Idle1 state.



| Specifications | 4TB | 3TB | 2TB | 1TB |
|---|--------------------|--------------------|--------------------|--------------------|
| Standard Model Numbers | ST4000VN008 | ST3000VN007 | ST2000VN004 | ST1000VN002 |
| Interface | SATA 6Gb/s | SATA 6Gb/s | SATA 6Gb/s | SATA 6Gb/s |
| Features and Performance | | | | |
| Drive Bays Supported | 1 – 8 Bays | 1 – 8 Bays | 1 – 8 Bays | 1 – 8 Bays |
| Multi-User Technology | 180 TB/year | 180 TB/year | 180 TB/year | 180 TB/year |
| Rotational Vibration (RV) Sensor | Yes | No | No | No |
| Dual-Plane Balance | Yes | Yes | Yes | Yes |
| Error Recovery Control | Yes | Yes | Yes | Yes |
| Max. Sustained Transfer Rate OD (MB/s) | 180MB/s | 180MB/s | 180MB/s | 180MB/s |
| Spindle Speed (RPM) | 5,900 | 5,900 | 5,900 | 5,900 |
| Cache (MB) | 64 | 64 | 64 | 64 |
| Reliability | | | | |
| Load/Unload Cycles ¹ | 600,000 | 600,000 | 600,000 | — |
| Non-recoverable Read Errors Rate, Max | 1 per 10E14 | 1 per 10E14 | 1 per 10E14 | 1 per 10E14 |
| Power-on Hours | 8,760 | 8,760 | 8,760 | 8,760 |
| Workload Rate Limit (WRL) | 180 | 180 | 180 | 180 |
| Mean Time Between Failures (MTBF, hours) | 1,000,000 | 1,000,000 | 1,000,000 | 1,000,000 |
| Limited Warranty (years) | 3 | 3 | 3 | 3 |
| Power Management | | | | |
| Startup Current, Typical (12V, A) | 1.8 | 2 | 2 | 1.2 |
| Average Operating Power (W) | 4.8 W | 4.8 W | 4.3 W | 3.76 W |
| Idling Average (W) | 3.95 W | 4.8 W | 3.56 W | 2.5 W |
| Standby Mode/Sleep Mode, Typical (W) | 0.5/0.5 | 0.5/0.5 | 0.5/0.5 | 0.5/0.5 |
| Voltage Tolerance, Inc. Noise (5 V) | ±5% | ±5% | ±5% | ±5% |
| Voltage Tolerance, Inc. Noise (12 V) | ±10% | ±10% | ±10% | ±10% |
| Environmental/Temperature | | | | |
| Operating (ambient, min °C) | 5 | 5 | 5 | 5 |
| Operating (drive case, max °C) ² | 70 | 70 | 70 | 70 |
| Non-operating (ambient, min °C) | -40 | -40 | -40 | -40 |
| Non-operating (ambient max °C) | 70 | 70 | 70 | 70 |
| Halogen-free | Yes | Yes | Yes | Yes |
| Environmental/Shock | | | | |
| Shock, Operating/Non-operating: 2 ms (max) | 80Gs/300Gs | 80Gs/300Gs | 80Gs/300Gs | 80Gs/300Gs |
| Environmental/Acoustics | | | | |
| Idle (typical) ³ | 2.3 bels | 2.3 bels | 1.9 bels | 2.1 bels |
| Seek (typical) | 2.5 bels | 2.5 bels | 2.1 bels | 2.3 bels |
| Physical | | | | |
| Height (mm/in) | 26.11 mm/1.028 in | 26.11 mm/1.028 in | 26.11 mm/1.028 in | 20.2 mm/0.795 in |
| Width (mm/in, max) | 101.85 mm/4.01 in | 101.85 mm/4.01 in | 101.85 mm/4.01 in | 101.85 mm/4.01 in |
| Depth (mm/in, max) | 146.99 mm/5.787 in | 146.99 mm/5.787 in | 146.99 mm/5.787 in | 146.99 mm/5.787 in |
| Weight (g/lb, typical) | 610 g/1.345 lb | 610 g/1.345 lb | 535 g/1.18 lb | 415 g/0.915 lb |
| Carton Unit Quantity | 20 | 20 | 20 | 25 |
| Cartons per Pallet / Cartons per Layer | 40/8 | 40/8 | 40/8 | 40/8 |

¹ Load/unload tested to 600,000 cycles.

² Seagate does not recommend operating at sustained case temperatures above 60°C. Operating at higher temperatures will reduce useful life of the product.

³ Idle measured in Idle1 state.

AMERICAS Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000
ASIA/PACIFIC Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888
EUROPE, MIDDLE EAST, AND AFRICA Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

© 2018 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. AgileArray and IronWolf are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. Seagate reserves the right to change, without notice, product offerings or specifications. DS1904.10-1807GB July 2018