





# CFast card reader for professional cinematographers

The RDF2 card reader is designed for professional cinematographers who pursue extreme transfer efficiency. It not only supports the next generation CFast 2.0 specification, but is also backward compatible with CFast 1.1 and CFast 1.0 memory cards.



# USB Type-A for great device compatibility

The RDF2 card reader is equipped with a micro USB (USB 3.1 Gen 1) port and includes a micro USB to USB Type-A cable to transfer data between your CFast memory cards and your computers.



Higher speeds, higher efficiency

Equipped with the USB 3.1 Gen 1 interface, the RDF2 card reader shows amazing transfer speeds, much faster than what you'd get with USB 2.0! The experts can boost their workflow efficiency by saving a significant amount of time transferring high-resolution files and focus on their professional work instead. In addition, it has an LED indicator to show card insertion and data transfer activity.





# USB 3.1 Gen 1 CFast 2.0 Card Reader **RDF**2

#### **Features**

- · USB 3.1 Gen 1 interface
- Supports CFast 2.0 / CFast 1.1 / CFast 1.0 memory cards
- · Compact and portable design
- Designed for high-resolution video, raw image transfers, and post-production processing
- Download the RecoveRx data recovery software from Transcend's official website



### RecoveRx software

Transcend o ers the RecoveRx software, a free data recovery utility that allows you to search deep within a storage device for traces of erased les including digital photos, documents, music, and videos.

_										
╰	n	Δ	$\boldsymbol{\mathcal{C}}$	ıΤ	$\Gamma$	2	tι	0	n	C
J	v	c	·		ı	и	u	$\circ$	11	2

Dimensions	67.6 mm x 45 mm x 15.2 mm (2.66" x 1.77" x 0.60")
Weight	26 g (0.91 oz)
Color	Black

USB Type	micro USB to USB Type A
Connection Interface	USB 3.1 Gen 1
Hardware	
Card Reader Slot(s)	CFast

Operating Environment						
Operating Temperature	0°C (32°F) ~ 70°C (158°F)					
Operating Voltage	5V					

Performance	
Note	Speed may vary due to host hardware, software, usage, and
	storage capacity.

Warranty		
Certificate	CE/FCC/BSMI/KC/RCM/EAC	
Warranty	Two-year Limited Warranty	

System Requireme	nt	
Operating System	Microsoft Windows 7	
	Microsoft Windows 8	
	Microsoft Windows 10	
	Mac OS X 10.2.8 or later	
	Linux Kernel 2.6.30 or later	

Compatibility			
Memory Card Supported	CFast 2.0		

## Ordering Information

TS-RDF2

Product specifications are subject to change without notice. Pictures shown may differ from actual products. When used as a storage capacity unit, one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment.



USB 3.1 Gen 1 Card Readers  Comparison	<b>⊕</b> Transcend	<b>®</b> transcend	⊕ Transcend	(f) transcend	© Pranscend
	RDC8	RDF9	RDF2	RDF8	RDF5*
Appearance					
Dimensions (Max.)		67.6 mm x 45 ı (2.66" x 1.	mm x 15.2 mm 77" x 0.60")		56 mm x 24 mm x 8.9 mm (2.20" x 0.94" x 0.35")
Weight (Max.)	32 g (1.13 oz)	30.6 g (1.08 oz)	26 g (0.91 oz)	32 g (1.13 oz)	18 g (0.63 oz)
Color	Black	Black	Black	Black/White	Black/White/Pink
Interface					
USB Type	micro USB to USB Type C	n	nicro USB to USB Ty	pe A	USB Type-A
Connection Interface			USB 3.1 Gen 1		
Hardware					
Card Reader Slot(s)	SD/microSD CompactFlash	SD/microSD CompactFlash	CFast	SD/microSD CompactFlash	SD/microSD
Warranty					
Warranty		Tv	vo-year Limited War	ranty	
0 111 111					
Compatibility	CDLIC (TILIC I)	CDLIC (LILIC II)	CFact 2.0	CDITC (TITIC I)	CDITIC (TITIC I)
Memory Card Supported	SDHC (UHS-I) SDXC (UHS-I)	SDHC (UHS-II) SDXC (UHS-II)	CFast 2.0	SDHC (UHS-I) SDXC (UHS-I)	SDHC (UHS-I) SDXC (UHS-I)
	microSDHC (UHS-I)	SDHC (UHS-I)		microSDHC (UHS-I)	microSDHC (UHS-I)
	microSDXC (UHS-I)	SDXC (UHS-I)			microSDXC (UHS-I)
	CompactFlash (UDMA7) r			CompactFlash (UDMA7	
	r	microSDXC (UHS-I)		•	
	Cor	mpactFlash (UDMA6	)		
	Cor	mpactFlash (UDMA7	")		
SD UHS-II	-	<b>✓</b>	-	-	-
SD UHS-I and below	<b>✓</b>	<b>✓</b>	-	<b>✓</b>	<b>✓</b>
microSD UHS-I and below	~	<b>✓</b>	-	<b>✓</b>	<b>✓</b>
CompactFlash UDMA5 and below	~	<b>✓</b>	-	<b>✓</b>	-
CompactFlash UDMA7 & UDMA6	~	<b>✓</b>	-	<b>✓</b>	-
CFast 2.0 and below	-	-	~	-	-

 ${}^{\star}\text{Note:}$  Simultaneous insertion of two cards not supported.