

# Mini Converter SDI to HDMI 6G



! 484 C98?0;=0; &Df =9 HD! F 6G 60=< B9> .98?0;= 1;97 &Df =9 HD! F 48 &D, HD, , 8/  
(6=, HD 19; 7, =< @340 /0-07 -0/482 , >/49 =9 HD! F, AE&/EB( 9; -, 6, 8. 0/ , 8, 692  
, >/49. +9> , 6<9 20= , /?, 8. 0/ 10, =>; 0< <>. 3 , < /9@8 .98?0;<498 19; 7 984-9;482  
(6=, HD 98 HD HD! F 7 984-9;< , < @066 , < ->46= 48 3D ( ' < : 6>< HD! F 48<=, 8= 69. 5  
19; 48<=, 8= ?4/09 /4<: 6, B @308 , 8 &Df 48: >= 4< .9880.=0/!

\$185

## Connections

SD+ Vide! + " &%\$  
1 A &D, HD 9; 6G &Df. 1 A A ' &Df  
F8: >= 19; , >=97 , =4. <@4. 3 9?0;  
41 7, 48 48: >= 1, 46<.

A all! g A&di! O&% " &%\$  
2 . 3, 880< 91 - , 6, 8. 0/ , 8, 692 , >/49.  
Digi%al A&di! O&% " &%\$  
4 . 3, 880< 91 AE&/EB( /424, 6 , >/49

M&I%i Ra%e S&" " ! #%  
A>=9 /0=0. =498 91 &D, HD 9; 6G &Df.

SD+ Vide! O&% " &%\$  
1 A &Df )4/09 99: #>=: >=.

SD+ Red& da % + " &%  
A>=97 , =4. , 66B <@4. 30< 9?0; 41 7, 48  
&Df 48: >= 4< 69<=.

U" da%e\$ a d C! \*g&#a%i!  
( &B

HDM+ Vide! O&% " &%\$  
HD! F =B: 0 A 9>=.

Recl! cki g  
+0<



## Standards

SD Vide! S%a da#d\$  
625450 \$A , 525459.94 " ' &C

HD Vide! S#a da#d\$  
720: 50, 720: 59.94, 720: 60,  
1080: 23.98, 1080: 24, 1080: 25,  
1080: 29.97, 1080: 30, 1080: 50,  
1080: 59.94, 1080: 60, 1080\$<F23.98,  
1080\$<F24, 1080\$<F25,  
1080\$<F29.97, 1080\$<F30, 1080!50,  
1080!59.94, 1080!60

2K Vide! S#a da#d\$  
2K DCF 23.98: , 2K DCF 24: ,  
2K DCF 25: 2K DCF 23.98\$<F,  
2K DCF 24\$<F, 2K DCF 25\$<F

UI#a HD Vide! S#a da#d\$  
2160: 23.98, 2160: 24, 2160: 25,  
2160: 29.97, 2160: 30

4K Vide! S#a da#d\$  
4K DCF 23.98: , 4K DCF 24: ,  
4K DCF 25:

SD+ C! m" lia ce  
&! \$' E 259! , &! \$' E 292! ,  
&! \$' E 296! , &! \$' E 372! ,  
&! \$' E 424! , &! \$' E 425! ,  
&! \$' E &' 2081

SD+ Vide! Ra#e\$  
&DF ?4/09 . 9880. =498< , ; 0 <@4. 3, -60  
-0=@008 <=, 8/, ; / /OE84498, 3423  
/OE84498, 0?0% A 9; 0?0% B 3G &DF  
, 8/ 6G &DF.

SD+ Vide! Sam" li g  
4:2:2 , 8/ 4:4:4

SD+ A&di! Sam" li g  
' 060?4<498 <=, 8/, ; / <, 7: 60 ; , =0 91  
48 5HC , 8/ 24 -4.

SD+ C! ! # P#eci\$!  
4:2:2 , 8/ 4:4:4

SD+ C! ! # S" ace  
+ ( ) , 8/ %GB  
  
SD+ A&#! S( i%chi g  
A>=97 , =4. , 66B /0=0. =< &D, HD  
9; 6G &DF.

HDM+ Vide! S#a da#d\$  
625!50 \$A , 525!59.94 " ' &C, 720: 50,  
720: 59.94, 720: 60, 1080: 23.98,  
1080: 24, 1080: 25, 1080: 29.97,  
1080: 30, 1080: 50, 1080: 59.94,  
1080: 60, 1080!50, 1080!59.94,  
1080!60, 2160: 23.98, 2160: 24,  
2160: 25, 2160: 29.97, 2160: 30

HDM+ C! ! # S" ace  
+ ( ) , 8/ %GB

HDM+ C! ! # P#eci\$!  
4:2:2 , 8/ 4:4:4

## Soft! are

SI f%( a#e C! ##! I  
! , . #& , 8/ \* 48/9@< <91=@, ; 0  
>: 2; , /0 ?4, ( &B.

+ %e# al SI f%( a#e U" g#ade  
)4, 48. 6>/0/ >: /, =0; , : : 64. , =498.

## Operating S"stems



! , . 10.12 &40;; ,  
! , . 10.13 H423 &40;; , 9; 6, =0; .



\* 48/9@< 8.1 9; \* 48/9@< 10.

## Settings Control

! 484 &@4. 30< 9; ( &B <91=@, ; 0.

## Po! er Requirements

+12) >84?0;<, 6: 9@0; <>: : 6B 48. 6>/0/  
@4-3 48=0; 8, =498, 6<9. 50= , /, : =0;< 19;  
, 66 . 9>8=; 40<. C, -60 =40 : 948=.

O" e#a%i! al VI !%age Ra ge  
12 18) DC

P! ( e# C! \$&m" %!  
5.2 \* , =<

## Physical Specifications



## Environmental Specifications

Operating Temperature  
0°C to 40°C (32°F to 104°F)

Storage Temperature  
-20°C to 45°C (-4°F to 113°F)

Relative Humidity  
0% to 90% (89% to 98%)

## What's Included

1 x SFP to HDMI 1.0  
1 x 3.5mm SATA to 2.5mm SATA Adapter

## Warranty

3-year limited warranty

A66 407 < 98 =34< @0-<40 , ;0 . 9: B;423= B6, . 5 7 , 24. D0<428 \$=B. =/. 2019, , 66 ;423=< ;0<0:?0/.  
A66 =, /07 , ;5< , ;0 : ;9: 0;=B 91=304; ;0<: 0.=4?0 9@80;<. ! &%%\$ 0A. 6>/0<< , 60<=, A0</>=40< , 8/ <34 : : 482 . 9<<<.  
' 34< @0-<40 ><0< ;0 7 , ;50=482 <0;?4. 0< =9 , /?0: =4<0 98 =34; / : , ;=B @0-<40< =9 : ;0?49>< ?4<4-9; < =9 9>; <4-0.  
+9> . , 8 9: = 9>= , = , 8B =470 -B . 3, 82482 . 99540 <0=482<. [\\$4? . B \\$9M.B](#)

Blackmagic Design Authori#ed Reseller