



HDMI HDBaseT Extender with Dual Output

VE814A

- ATEN VE814A is an HDBaseT Video Extender that is capable of sending HDMI signals up to 100 m over a single Cat 5e/6/6a or ATEN 2L-2910 Cat 6 cable. Featuring dual synchronous outputs, the VE814A can transmit video signal to two remote displays and one at the local side. This HDCP 2.2-compliant extender meets the HDMI Specification, including 3D, Deep Color, the maximum data rate of (10.2 Gbps), and 4K video quality up to 100 m.


The VE814A supports RS-232 and IR signaling pass-through, allowing you to control the HDMI source device from the remote unit (VE814AR) while granting access to the HDMI display device from the local unit (VE8014AT). In addition, it supports Long Reach Mode that extends HDMI signals up to 150 m, 1080p, via a single Cat 5e/6 cable.

The VE814A is a powerful solution for where digital signage is required, such as bars, educational spaces, and public transportation stations, allowing display of identical contents at different spots.



Features

- Extends HDMI signals to one local and two remote displays up to 100 m over a single Cat 5e/6/6a or ATEN 2L-2910 Cat 6 cable
- HDMI (3D, Deep Color, 4K); HDCP 2.2 compatible
- Superior video quality:
 - 4K up to 100 m
 - 1080p up to 150 m when in HDBaseT Long Reach Mode
- Extends Ethernet communication using the Ethernet pass-through port
- Supports two IR channels for simultaneous IR signal transmissions, ranged from 30 KHz to 56 KHz
- ATEN EDID Technology -- when both transmitter and receiver sides are connected, VE814A adopts the EDID values of the display connected to the VE814AT for high-quality output
- RS-232 channel – allows you to connect to serial terminals or serial devices, such as touch screens and barcode scanners
- Supports wide screen format
- Built-in 8 kV/15 kV ESD protection
- Plug-and-play
- Rack-mountable



Specifications

| Function | VE814AR | VE814AT |
|--|---|-------------------------------------|
| Video Input | | |
| Interfaces | N/A | 1 x HDMI Type A Female (Black) |
| Impedance | N/A | 100 |
| Max. Distance | N/A | 1.8 m |
| Video Output | | |
| Interfaces | 2 x HDMI Type A Female (Black) | 1 x HDMI Type A Female (Black) |
| Impedance | 100 Ω | 100 Ω |
| Video | | |
| Max. Data Rate | 10.2Gbps (3.4Gbps per lane) | |
| Max. Pixel Clock | 340 MHz | |
| Compliance | HDMI (3D, Deep Color, 4K); HDCP Compatible Consumer Electronics Control (CEC) | |
| Max. Resolutions / Distance | Up to 4K@70m (Cat 5e/6) / 100m (Cat 6a/ATEN 2L-2910 Cat6); 1080p@100m (Cat 5e/6/6a) *4K supported: 4096 x 2160 / 3840 x 2160 @ 60Hz (4:2:0); 4096 x 2160 / 3840 x 2160 @ 30Hz (4:4:4) | |
| Audio | | |
| Input | N/A | 1 x HDMI Type A Female (Black) |
| Output | 2 x HDMI Type A Female (Black) | 1 x HDMI Type A Female (Black) |
| Connectors | | |
| Unit To Unit | 1 x RJ-45 Female | 1 x RJ-45 Female |
| Power | 1 x DC Jack (Black) with locking | 1 x DC Jack (Black) with locking |
| Control | | |
| RS-232 | Connector: 1 x Terminal Block, 3 pole; Baud Rate: 115200 bps, Data Bits:8, Stop Bits:1, no parity and flow control | |
| IR | 2 x Mini Stereo Jack Female (Black) | 2 x Mini Stereo Jack Female (Black) |
| Ethernet | 1 x RJ-45 Female | 1 x RJ-45 Female |
| Switches | | |
| Long Reach Mode Switch | 1 x Slide Switch - ON/OFF | 1 x Slide Switch - ON/OFF |
| Firmware Upgrade | 1 x Slide Switch - ON/OFF | 1 x Slide Switch - ON/OFF |
| Power Consumption | | |
| | DC 5V, 7.9W | DC 5V, 5.1W |
| Environmental | | |
| Operating Temperature | 0° to 40° C | 0° to 40° C |
| Storage Temperature | -20° to 60° C | -20° to 60° C |
| Humidity | 0 - 80% RH, Non-Condensing | 0 - 80% RH, Non-Condensing |
| Physical Properties | | |
| Housing | Metal | Metal |
| Weight | 0.47 kg | 0.45 kg |
| Dimensions (L x W x H) with bracket | 14.04 x 12.30 x 3.00 cm | 14.04 x 12.30 x 3.00 cm |
| Dimensions (L x W x H) without bracket | 13.60 x 10.10 x 2.90 cm | 13.60 x 10.10 x 2.90 cm |

Note: We strongly recommend that you use ATEN 2L-2910 Cat 6 cable for best product performance

Product information is subject to change without prior notice.

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com

Publish Date: 11/2018 V3.0



© Copyright 2018 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.