



2m Reinforced USB Type C to Lightning Cable

No.: 31287

USB Typ C Male to Lightning Male

Description

- High strength USB 2.0 Type C charge & sync cable for iPhones, iPads and other Apple devices
- Apple MFi licensed product (Made for iPhone / iPad / iPod)
- Quickly charge mobile devices with PD 2.0
- Reinforced with aramid and HMPE fibres to provide a high strength cable solution
- Optimised strain relief to withstand over 100,000 bending cycles, 2 year warranty

Lindy's range of reinforced USB charging cables provide a reliable and effective charging solution for a variety of devices, while avoiding the common issues of standard or cheaper charging cables such as cable fraying, snapping and low charging speeds.

With aramid fibres, commonly used in aerospace and military applications, housed within the cable itself, these cables possess an optimised high strength quality not seen with standard USB cables, and combined with HMPE fibre braiding, a material well used for fishing ropes and lines, common cable faults from daily use are no longer an issue. The specialised Lindy strain relief also enhances the durability of these cables, tested to bend over 100,000 times before failure, a revolutionary resistant yet flexible solution to prevent splitting and snapping.

This range of USB 2.0 Type C to Lightning cables provides a fast, reliable, efficient charge charge to iPhone, iPad and other apple devices with PD 2.0, utilising not only a reinforced shielding and jacket structure but also an optimum internal build including copper shielding , to support high quality, fast charging.

The cable also comes supplied with a Lindy hook-and-loop tie wrap, providing a neat, handy solution to avoid the cable tangling.

Technical details

Connectors

- Connector A: USB Type C Male
- Connector B: Lightning Male
- Housing Material: TPE
- Connector Plating: Nickel
- Pin Construction: Copper
- Pin Plating: Gold Plated
- Dimensions (approx.) WxDxH: USB Type C: 11.5x15x6mm (0.45x0.59x0.24in)

Lightning: 11x34x6mm (0.43x1.34x0.24in)

Cable Construction

- Length: 2m (6.56ft)
- Standard: USB 2.0
- Colour: Black
- Type: Round
- Jacket Diameter: 3.5mm (0.14in)
- Jacket Material: TPE with HMPE Braid
- Conductor Material: Copper
- Conductor Gauge: Data: 32AWG
Power: 24AWG
- Shielding: Tinned Copper Shielding

Specifications

- Supported Bandwidth: 480Mbps
- Power Delivery: PD 2.0
- Nominal Attenuation: 0.5Mhz – 400Mhz < 5.8db
- Minimum Bend Radius: 35mm (1.38in)
- Operating Temperature: 0°C - 60°C (32°F - 140°F)
- Storage Temperature: 0°C - 70°C (32°F - 158°F)

Miscellaneous

- Packaging Type: Polybag
- Warranty (Years): 2
- Certificated: MFI, RoHS and REACH

Purchasing Information

- No.: 31287
- EAN: 4002888312875

© LINDY 2020