



## SuperSpeed USB Dual Monitor Multiport Adapter

USB 3.2 Gen 1 Type-A Male to HDMI (up to 2048x1152@60Hz) Female, VGA (up to 2048x1152@60Hz) Female, Two SuperSpeed USB-A Ports, Gigabit RJ45 Port and USB Micro-B Power Port; Aluminum, Black

Part No.: [152846](#)

EAN-13: 0766623152846 | UPC: 766623152846

### An all-in-one USB Dual Monitor Multiport Adapter for reliable connections to your displays and devices

The Manhattan SuperSpeed USB Dual Monitor Multiport Adapter turns your USB device into more complete and accessible hardware. It helps you do more with the devices you already have to increase productivity nearly anywhere you are. This multiport adapter helps you expand your workspace or share what you're working on with an included 2048x1152@60Hz HDMI port that connects to your existing HDMI display (or monitor, projector, etc.) and a 2048x1152@60Hz VGA port that connects to a legacy VGA display. Both displays can be used simultaneously. You can add up to two peripherals, such as a mouse, keyboard, hub, external memory device and more, with its two SuperSpeed USB-A ports. And if you need a wired connection to a network, it offers gigabit speeds at its built-in Ethernet port. This adapter is a perfect companion to MacBook® and other computers since it expands your access to devices through one USB port.

### Superior, easy connections to Ethernet, your HDMI and VGA displays and USB peripherals

The Manhattan SuperSpeed USB Dual Monitor Multiport Adapter is easy and quick to install. This adapter enhances the functionality of your USB device right when you connect it — there are no settings to configure or additional steps to get your devices working with it. Its design gives you a compact, complete solution that eliminates unnecessary cables, tangles and clutter to keep your workspace neat and tidy.

## Multiport Adapter that's made to go where you go

Sturdy aluminum housing makes this multiport adapter the perfect travel companion. Simply slip it into your backpack or computer bag with your main device, and you always have a way to connect to the available compatible devices and display you use to get work done.

### Features:

- Durable, portable and powerful dual-monitor hub that connects you to the network, your displays and multiple USB devices over a USB-A connection
- One HDMI port (2048x1152@60Hz), one VGA port (2048x1152@60Hz), two USB 3.2 Gen 1 type-A ports, 10/100/1000 Mbps Ethernet port and a USB Micro-B power port
- Supports dual monitor extended mode on Mac OS 10.8 or above
- Supports up to 2K@60Hz resolution in Mirror or Extended mode\*
- HDMI and VGA ports can be used simultaneously in mirrored or extended mode
- Up to 5 Gbps data transfer speed following USB 3.2 Gen 1 ports
- Gigabit speeds (10/100/1000 Mbps) on Ethernet port
- Durable aluminum housing, making it the perfect desktop or travel companion
- Plug and play
- Three-year warranty
- \*When both display ports are used simultaneously, the HDMI port offers 2K@60Hz resolution and the VGA port offers 1080p@60Hz resolution

### Specifications:

#### Standards and Certifications

- USB 3.2 Gen 1
- HDMI 1.3
- VGA
- CE
- FCC
- RoHS2
- WEEE

#### General

- Video Resolutions:
  - 640 x 480
  - 800 x 600
  - 1024 x 768
  - 1920 x 1080 (1080p@60Hz)
  - 1920 x 1200
  - 2048x1080 (2K@60Hz)
  - 2048 x 1152p at 60 Hz

- USB-A ports: 5 Gbps
- Gigabit Ethernet port: 10/100/1000 Mbps
- 30-AWG cable gauge
- USB micro-B power port
- Mylar and aluminum shielding
- Withstanding voltage: 100 VDC
- Insulation resistance: 2 MOhm
- Conductive resistance: 5 Ohm

#### Connections

##### Input:

- One USB-A, male

##### Outputs:

- One HDMI, female
- One VGA, female
- One 10/100/1000 Mbps RJ45, female
- Two USB-A, female
- One USB Micro-B, female

#### Physical

- Dimensions: 119.6 x 42.8 x 14.15 mm (4.71 x 1.69 x 0.56 in.)
- Cable Length: 20 cm (7.87 in.)
- Weight: 81.5 g (2.87 oz.)
- Housing: aluminum

#### Operating Environment

- Operation Temperature: 0 – 45°C (32 – 113°F)
- Storage Temperature: -10 – 70°C (14 – 158°F)
- Humidity (noncondensing): 10 – 90%

#### System Requirements

- Windows 7/8.1/10
- Mac OS 10.8 or above

#### Package Contents

- SuperSpeed USB Dual Monitor Multiport Adapter
- Quick Instruction Guide



