

PoE Injector

MODEL: TL-POE150S Datasheet

Features


- Complies with IEEE802.3af standard
- Cost saving, no power cabling for Ethernet network device
- Delivers power and data over the single cable up to 100 meters
- Advanced Auto-Sensing Algorithm enables providing power with 802.3af PD
- Supports power classification, Auto-determine the necessary power requirements
- High safety with Short Circuit Protection
- Plug & Play installation, requires no configuration
- External 48VDC power supply




Overview

The PoE Injector TL-POE150S fully complies with IEEE 802.3af standard, and can work with all IEEE 802.3af PoE compliant PDs (Powered Devices) or PoE Receiver Adapters, such as TP-Link's TL-POE10R, or other equivalent product, to expand your network to where there are no power line or outlet, where you wish to fix device such as AP, IP Camera or IP Phone, etc.

Specifications

| | |
|--------------------------|---|
| Product Picture |  |
| Model | TL-POE150S |
| Standards | IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3af |
| Ports | 1 10/100/1000Mbps Auto-Negotiation RJ45 LAN port(LAN IN) 1 10/100/1000Mbps Auto-Negotiation RJ45 PoE port(POWER+DATA OUT) 1 power socket(DC IN) |
| Network Media | 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 100BASE-TX: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 1000BASE-T: UTP category 5, 5e, 6 cable(maximum 100m) |
| Basic Function | Auto-Sensing Algorithm enables providing power with 802.3af PD Delivers power and data over the single cable up to 100 meters Auto-determine the necessary power requirements Plug-and-Play |
| Power | Input: External 48VDC power adapter Output: Auto-determine the necessary Power requirements(max. 15.4W) |
| LED Indicator | ON: Supplying power normally Flashing: NO PD connected/Supplying power abnormally Off: No power supply |
| Dimensions (W x D x H) | 80.8 x 54 x 24mm |
| Certification | FCC, CE, RoHS |
| Package Contents | TL-POE150S, Power Adapter, RJ45 cable, Installation Guide |
| Environment | Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90%RH non-condensing Storage Humidity: 5%~90%RH non-condensing |

Diagram



Package:

- TL-POE150S PoE Injector
- One Ethernet (CAT.5 UTP) Cable
- One Power Adapter
- User Guide

Related Products:

- Load Balance Broadband Router TL-R470T+
- AC750 Wireless Gigabit Access Point AP200
- PoE Splitter TL-POE10R

www.tp-link.com

Specifications are subject to change without notice. TP-Link is a registered trademark of TP-Link Technologies Co., Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders. Copyright © 2017 TP-Link Technologies Co., Ltd. All rights reserved.