

AUTHPOINT HARDWARE TOKEN



DATASHEET

AuthPoint's time-based, one-time password (OTP) hardware token is a sealed electronic device designed to generate secure OTPs every 30 seconds that businesses can use as an alternative to the mobile token to authenticate into protected resources.

MAXIMUM FLEXIBILITY AND SECURE ONE-TIME PASSWORD (OTP) AUTHENTICATION

WatchGuard hardware tokens are ready to use and can provide an additional source of protection for businesses when mobile device use is limited or restricted. Provisioning is fast and easy through the self-service portal. Just ship the token and the users will self-associate and activate.

YOUR TOKEN SECRETS ARE PROTECTED

Most solutions require you to import the token secrets - also called "seeds" - completely exposed. It means that anyone that has a copy of the le or made the importation can create a software clone. The AuthPoint Hardware token seeds are never exported or exposed. The entire activation process is Cloudbased, which means sensitive data is not exposed.


COMMON USE CASES

Although mobile-based authentication is more popular and, in many cases, more secure, there are many scenarios where hardware tokens are required or preferred.

- Accessing locations where authentication is required, but mobile use is restricted, like hospitals
- Tough environments, like mines or oil platforms
- Companies with policies that limit or restrict use of personal mobile device for security purposes

KEY FEATURES

- Ready to use with a one-step activation process
- 3-year warranty, 7+ year life expectancy
- Automatically provisioned through WatchGuard Cloud



DEVICE SPECIFICATIONS		
Product Dimensions	2.52″ x 1.57″ x 0.47″ (64 x 40 x 12 mm)	
Product Weight	0.04 lbs (18 g)	
Lifetime	7+ years when used in full (CR2032 battery)	
Seed Records	Never exported or exposed	
Physical Security	Tamper-evident ultrasonic sealing of enclosure	
Buttons	Two Buttons: 1 - for on/o 2 - change the OTP format (12 34 56 / 123456 / 123 456)	
Password Generation	Electronic One-Time Password generation based on time	
Password Algorithm	OATH Time-Based One-Time Password Algorithm (TOTP) – RFC 6238	
Certi cations	includes RoHS, FCC, CE, and KCC	
Packaging	Ten units per box	
ENVIRONMENT	OPERATING	STORAGE
Storage Temperature	32° F to 113° F (0° C to 45° C)	14° F to 122° F (-10° C to 50° C)

Contact your authorized WatchGuard reseller or visit www.watchguard.com to learn more.

U.S. SALES 1.800.734.9905 INTERNATIONAL SALES +1.206.613.0895 WEB www.watchguard.com

WatchGuard Technologies, Inc.

85% non-condensing

No express or implied warranties are provided for herein. All speci cations are subject to change and expected future products, features or functionality will be provided on an if and when available basis. ©2021 WatchGuard Technologies, Inc. All rights reserved WatchGuard, the WatchGuard logo, Firebox and AuthPoint are registered trademarks of WatchGuard Technologies, Inc. in the United States and/or other countries. All other tradenames are the property of their respective owners. Part No. WGCE67344_041421