





TFX POWER 3

300W

IDEAL APPLICATIONS

Mini and media PC systems Systems with low installation depth Classic office and web applications

HIGHLIGHTS

80 PLUS® Gold / Bronze efficiency (up to 91.7 / 88.3%) Up to two strong dual 12V-rails Compact and space-saving design Sleeved or flat black cables for convenient usage

Compact And Silent Energy

TFX Power 3 300W: the upgraded be quiet! high-efficiency PSU for mini and media PCs with great features at a reasonable price.

Highlights »

- Certified 80 PLUS Gold and Bronze efficiency (up to 91.7%)
- High stability and PCle graphics card support
- 300W of continuous power
- High-quality temperature-controlled 80mm fan for low-noise operation
- Sleeved or flat black cables up to 60cm long
- Meets the latest safety and efficiency requirements
- Standby draw less than 0.17 watts
- Three-year manufacturer's warranty
- Product conception, design and quality control in Germany







TFX POWER 3

COMPACT AND SILENT ENERGY

Techni	ical Data »				
	Model	300W Gold	300W Bronze		
	Article no.	BN323	BN322		
	EAN Code	4260052188293	4260052188286		
	Voltage (Vac) / Frequency (Hz)	100 - 240 / 50 - 60	100 - 240 / 50 - 60		
	Dimensions (L x W x H)	175 x 85 x 65	175 x 85 x 65		
	TFX 12V 2.52 / EPS 12V 2.92	v/v	√ / √		
	Wire-free (DC-side)	-	-		
_	Silence-optimized be quiet! fan (mm)	80	80		
IERA	Noise level (dB(A)) at 20 / 50 / 100% load	9.7 / 12.4 / 21.7	14.6 / 15.4 / 29.1		
IN GENERAL	12V rail (Multi-Rail) / 12V Single Rail	2/-	-1 •		
2	Overclocking Key / Jumper	-/-	-/-		
	Power Good signal	100-150ms	100-150ms		
	PFC	active	active		
	Certification / Efficiency (%) at 230V	80 PLUS [®] Gold / 91.7%	80 PLUS [®] Bronze / 88.3%		
	Energy Star 7.0 compatible	•	✓		
	ErP ready / Power in stand-by (W)	√ / <0.17	√ / <0.14		
	OCP, OVP, UVP, SCP, OPP, OTP	•	→		
	Lifetime of PSU at 25°C (h)	100,000	100,000		
	No. of cables	5	5		
	Maximum cable length (cm)	60	60		
CABLES	Length of ATX-connection cable (cm)	35	35		
CAB	Cable management	Fixed	Fixed		
	Sleeved cables	20+4 pin	20+4 pin		
	Flat cables	PCIe, drives, P4	PCIe, drives, P4		
CONNECTORS	ATX motherboard (20+4-pin)	•	·		
	PCI express (6+2-pin)	1	1		
	P8-/P4-connector	-/1	-/1		
NNE	SATA	3	3		
8	PATA	2	2		
	FDD (Floppy)	1	1		

Output Dat	a »
------------	-----


AC Input		100-240Vac 50-60Hz 6-2.5A					
DC Output		3.3V	5V	12V1	12V2	-12V	5VsB
	Max. Current Max. Combined Power	18A	18A	13A	13A	0.3A	3A
300W Gold				24A		U.3A	JA
300W Gold		103W		288W		3.6W	15W
		300W					

AC Input		100-240Vac 50-60Hz 5-2A					
DC Output		3.3V	5V	12V1	-12V	5VsB	
	Max. Current	16A	16A	25A	0.3A	2.5A	
300W Bronze				25A	U.3A		
300W Bronze	Max. Combined	85W		300W	3.6W	12.5W	
	Power	300W					




TFX POWER 3

COMPACT AND SILENT ENERGY



Logistics	Logistics data »					
Region	Model	Article no	EAN code			
EU	TFX Power 3 300W Gold	BN323	4260052188293			
EU	TFX Power 3 300W Bronze	BN322	4260052188286			





Contact »	
be quiet! Headquarters	Service hotline: +49 40 7367 686 44
Listan GmbH	e-mail: service@bequiet.com
Wilhelm-Bergner-Straße 11c 21509 Glinde Germany	Visit the contact section on bequiet.com for the right regional service information.