

# FIREBOX M290 & M390

Up to 2.4 Gbps UTM throughput

# ENTERPRISE-GRADE SECURITY FOR SMALL TO MIDSIZE BUSINESSES

Because smaller companies are generally less protected and easier to break into, small business has become the new big target for cyberattacks. The Firebox M290 and M390 rewalls are specil cally engineered to defend all types of small businesses against attacks that are no less erce than those targeting larger organizations. Our unique product architecture enables small and midsize businesses to leverage best-in-class security services – from URL Itering and intrusion prevention to application control and ransomware prevention, minus the cost and complexity of multiple single-point solutions.



"WatchGuard Firebox M series rewalls are well-suited for businesses with rapidly evolving networks who need defense against the latest threats. They o er a remarkable range of security features, intuitive management, and throughput your users need to keep up with the pace of business." - Hayden Johnston, Operations Director at WYSCOM

# QUICK AND SIMPLE DEPLOYMENT

With WatchGuard Cloud, IT sta can create and store conguration data in the Cloud (public or private) and have the appliance directly shipped to its destination. Once the device arrives, it can connect to the Cloud for a secure download of its conguration settings, saving your stat travel time and money.

# AUTOMATION TO THE CORE

WatchGuard Firebox M Series appliances are designed with automation to the core, allowing your IT team to do more with less. The WatchGuard Automation Core makes it possible to deploy from the Cloud, block threats, update signatures, and detect and kill malware, all without lifting a nger.

# UNIFIED SECURITY DEFEATS COMPLEXITY

The WatchGuard Uni ed Security Platform<sup>™</sup> is a true force multiplier for IT teams. It makes operational ease possible by integrating the WatchGuard Firebox with WatchGuard's authentication, endpoint security, and Wi-Fi solutions to enable comprehensive, multi-layered security. Unifying security into a single platform unlocks e ciencies simply not possible with siloed systems, allowing for automation of frequent manual tasks that take up time.

# A CLOUD'S-EYE VIEW OF YOUR ENTIRE NETWORK

WatchGuard Cloud provides full visibility into your network so that you can make timely, informed, and e ective decisions about your network security anywhere, anytime. The platform displays 100+ dashboards and reports that allow you to quickly see high-level trends and anomalies, then drill down into detailed information on each.

# EXPANSION MODULES FOR GREATER PORT DENSITY

The Firebox M Series provides expansion bays that can be used to add network modules to de ne a con guration that meets the needs of almost any network con guration. Each appliance has an open module bay for expansion modules, with options for 4 x 1 Gb copper, 4 x 1 SFP, 2 x 1 SFP+, or 4 port multispeed ports. Network modularity empowers IT pros to customize the port con guration to meet their needs, while ensuring the exibility to adapt the rewall as their network evolves.

# **FEATURES & BENEFITS**

- Enterprise-grade prevention, detection, correlation and response from the perimeter to the endpoint with our Total Security Suite.
- Gain critical insights about network security, from anywhere and at any time, with WatchGuard Cloud.
- Built-in compliance reports, including PCI and HIPAA, mean one-click access to the data you need to ensure compliance requirements are met.
- Up to 18 Gbps rewall throughput. Turn on all additional security services and still see up to 2.4 Gbps throughput.

Firebox	M290	M390	
THROUGHPUT 1			
UTM (full scan) 2	1.18 Gbps	2.4 Gbps	
VPN (IMIX)	800 Mbps	1.8 Gbps	
HTTPS Content Inspection (IPS enabled) 3	696 Mbps	1.32 Gbps	
Antivirus	1.47 Gbps	3.1 Gbps	
IPS (full scan)	1.3 Gbps	3.3 Gbps	
Firewall (UDP 1518)	5.8 Gbps	18 Gbps	
VPN (UDP 1518)	2.4 Gbps	5.2 Gbps	
CAPACITY			
Interfaces 10/100/1000 4	8x1 Gb	8x1 Gb	
I/O interfaces	1 serial/2 USB	1 serial/2 USB	
Concurrent connections	3,500,000	4,500,000	
New connections per second	34,000	98,000	
VLANs	100	250	
WSM licenses (incl)	4	4	
TDR Host Sensors included	75	150	
VPN TUNNELS			
Branch O ce VPN	75	250	
Mobile VPN	75	250	
SECURITY FEATURES			
Firewall	Stateful packet inspection, TLS decryption, proxy rewall		
Application proxies	HTTP, HTTPS, FTP, DNS, TCP/UDP, POP3S, SMTPS, IMAPS and Explicit Proxy		
Threat protection	DoS attacks, fragmented & malformed packets, blended threats		
Filtering options	Browser Safe Search, Google for Business		
VPN			
Site to Site VPN	IKEv2, IPSec, Policy and Route Based Tunnels, TLS hub and spoke		
Remote Access VPN	IKEv2, IPSec, L2TP, TLS		
VISIBILITY			
Logging and noti cations	WatchGuard Cloud & Dimension, Syslog, SNMP v2/v3		
Reporting	WatchGuard Cloud includes over 100 pre-de ned reports, executive summary and visibility tools		
CERTIFICATIONS			
Security	Pending: Common Criteria,	FIPS 140-3	
Safety	NRTL/CB		
Network	IPv6 Ready Gold (routing)		
Hazardous substance control	WEEE, RoHS, REACH		
NETWORKING			
SD-WAN	Multi-WAN failover, dynamic path selection, jitter/loss/latency measurement		
Dynamic Routing	RIP, OSPF, BGP		
High Availability	Active/passive, active/active		
QoS	802.1Q, DSCP, IP Precedence		
Tra c Management	By policy or application		
IP address assignment	Static, DHCP (server, client, relay), PPPoE, DynDNS		
NAT	Static, dynamic, 1:1, IPSec traversal, policy-based		
Link aggregation	802.3ad dynamic, static, active/backup		

1 Throughput rates are determined using multiple ows through multiple ports and will vary depending on environment and conguration. Max rewall throughput tested via direct connection using 1518 byte UDP frame based on RFC 2544 methodology. All testing performed on Fireware version 12.7.2

2 UTM throughput is measured using HTTP tra c with AV, IPS, and Application Control enabled, and does not account for all security services available on the appliance.

3 HTTPS throughput is measured per NetSecOPEN methodology - 256k response with TLS1.2 AES256 + SHA-256.

Sirebox M390	Model Metwork Interfaces   LEDs Reset USB Network Interfaces   Cooling Fans Power Supply On/Off Switch   OWER M290 M390   ns 12.08" x 17.24" x 1.73" (307 mm X 438 mm x 44 mm) 12.08" x 17.24" x 1.73" (307 mm X 438 mm x 44 mm)   8.04 lbs (3.65 kg) 8.04 lbs (3.65 kg) 8.04 lbs (3.65 kg)   on 22.71" x 8.14" x 17.44" (588 mm x 648 mm x 200 mm) 22.71" x 8.14" x 17.44" (588 mm x 648 mm x 200 mm)   11.53 lbs (5.23 kg) 11.53 lbs (5.23 kg) 11.53 lbs (5.23 kg)   Single PSU -65W 90-264VAC-, 1.0A/1.5A, 47-63Hz Single PSU -120W 90-264VAC-, 2.2A/2.4A, 47-63Hz	
LEDs Power switch	Reset USB Network Interfaces	
	COO I	
	Cooling Fans Power Supply	y On/Off Switch
PHYSICAL AND POWER SPECIFICATIONS	M290	M390
Product Dimensions (W x D x H)		
Product Weight	8.04 lbs (3.65 kg)	8.04 lbs (3.65 kg)
Shipping Dimension (W x D x H)		
Shipping Weight	11.53 lbs (5.23 kg)	11.53 lbs (5.23 kg)
Power	90-Ž64VAC~, 1.0A/1.5A,	90-Ž64VAC~, 2.2A/2.4A,
Power Consumption		
MTBF	623,087 hours	578,655 hours
ENVIRONMENT	OPERATING	STORAGE
Temperature		
Relative Humidity	5% to 90%	5% to 90%

#### STRONG SECURITY AT EVERY LAYER

Altitude

Uniquely architected to be the industry's smartest, fastest, and most e ective network security products, WatchGuard solutions deliver in-depth defenses against advanced malware, ransomware, botnets, trojans, viruses, drive-by downloads, phishing and much more. Total and Basic Security Suite packages are available on all Firebox solutions.

non-condensing 0 to 15,000 ft at 95°F (4,570 m at 35°C)

non-condensing

0 to 9,843 ft at 95°F (3,000 m at 35°C)

	SUPPORT	BASIC SECURITY	TOTAL SECURITY
Stateful Firewall	1	1	1
VPN	$\checkmark$	1	1
SD-WAN	1	$\checkmark$	1
Access Portal*	$\checkmark$	$\checkmark$	1
Intrusion Prevention Service (IPS)		$\checkmark$	1
Application Control		$\checkmark$	1
WebBlocker		$\checkmark$	1
spamBlocker		$\checkmark$	1
Gateway AntiVirus		$\checkmark$	1
Reputation Enabled Defense		$\checkmark$	1
Network Discovery		1	1
APT Blocker			1
Threat Detection & Response			1
DNSWatch			1
IntelligentAV*			1
WatchGuard Cloud Visibility Data Retention		1 Day	30 Days
Support	Standard (24 x 7)	Standard (24 x 7)	Gold (24 x 7)

\* Total Security Suite required for Firebox V and Firebox Cloud.

#### For details, talk to your authorized WatchGuard reseller or visit www.watchguard.com.

 $\rm 4\,Firebox\,M290$  and M390 ship with one empty bay that can accommodate one of the following: 4 x 1 Gb copper, 4 x SFP Iter, 2 x SFP+ ber, 4 x 10 Gb multi-speed ports. PoE+ not supported on M290 and M390.

Contact your WatchGuard reseller or call WatchGuard directly (1.800.734.9905) for help determining the right model for your network. Visit www.watchguard.com/sizing to access the online Product Sizing Tool.

U.S. SALES 1.800.734.9905 INTERNATIONAL SALES +1.206.613.0895 WEB www.watchguard.com

WatchGuard Technologies, Inc.

No express or implied warranties are provided for herein. All speci cations are subject to change and expected future products, features or functionality will be provided on an if and when available basis. ©2021 WatchGuard Technologies, Inc. All rights reserved. WatchGuard, he WatchGuard logo, Fireware, and Firebox are registered trademarks of WatchGuard Technologies, Inc. in the United States and/or other countries. All other trademarks are the property of their respective owners. Part No. WGCE67522\_100121