



## ASUS ROG THOR 1600W Titanium power supply unit 20+4 pin ATX ATX Black, Silver

**Brand :** ASUS

**Product code:** 90YE00K0-B0NA00

**Product name :** ROG THOR 1600W Titanium



ROG-THOR-1600T-GAMING

ASUS ROG THOR 1600W Titanium. Total power: 1600 W, AC input voltage: 100 - 240 V, Combined power (+3.3V): 100 W. Motherboard power connector: 20+4 pin ATX, Cabling type: Fully-Modular. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Titanium. Product colour: Black, Silver, Cooling type: Active, Fan diameter: 13.5 cm. Cables included: AC, CPU, PCIe, Peripheral (Molex), SATA



Power		Ports & interfaces	
Total power *	1600 W	Cabling type	Fully-Modular
AC input voltage *	100 - 240 V	<b>Performance</b>	
Combined power (+3.3V)	100 W	80 PLUS certification *	80 PLUS Titanium
Combined power (+12V)	1600 W	Purpose *	PC
Combined power (+5V)	100 W	Power supply unit (PSU) form factor *	ATX
Combined power (-12V)	3.6 W	<b>Design</b>	
Combined power (+5Vsb)	15 W	Product colour	Black, Silver
Max output current (+3.3V)	20 A	Cooling type	Active
Max output current (+12V)	133.3 A	Fan diameter	13.5 cm
Max output current (+5V)	20 A	Illumination	✓
Max output current (-12V)	0.3 A	On/off switch	✓
Max output current (+5Vsb)	3 A	<b>Packaging content</b>	
Power protection features	Over power, Overcharge, Overheating, Overload, Short circuit, Under voltage	Cables included	AC, CPU, PCIe, Peripheral (Molex), SATA
<b>Ports &amp; interfaces</b>		Cable tie(s) included	✓
Motherboard power connector *	20+4 pin ATX	<b>Weight &amp; dimensions</b>	
Number of SATA power connectors	12	Width	190 mm
Peripheral (Molex) power connectors (4-pin) *	6	Depth	150 mm
PCI Express power connectors (6+2 pin)	10	Height	86 mm
PCI Express power connectors (16-pin)	1	Weight	2.69 kg
CPU P4 connector (4-pin)	2	<b>Packaging data</b>	
CPU power connector (4+4 pin)	✓	Package weight	2.71 kg
ATX power connector (20+4 pin)	✓	Package type	Box
<b>Technical details</b>		Sustainability compliance	✓
		Compliance certificates	CE, Low Voltage Directive (LVD), RoHS
<b>Logistics data</b>		Harmonized System (HS) code	84733020



4711081198390

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 04-NOV-2024. Prints or copies of Information are only valid on the printed Publication date