



Philips V Line 275V8LA/00 computer monitor 68.6 cm (27") 2560 x 1440 pixels Quad HD LED Black

Brand : Philips

Product family: V Line

Product code: 275V8LA/00

Product name : 275V8LA/00

Monitor 275V8LA LCD monitor

Philips V Line 275V8LA/00 computer monitor 68.6 cm (27") 2560 x 1440 pixels Quad HD LED Black:

Philips V line wide-view monitor gives viewing beyond boundaries, great value with essential features. Adaptive-Sync delivers smooth video display. Features like anti-glare, LowBlue mode and flicker-free for easy-on-the-eyes.

Philips V Line 275V8LA/00. Display diagonal: 68.6 cm (27"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LED, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). VESA mounting. Product colour: Black



Display		Ergonomics	
Display diagonal *	68.6 cm (27")	Tilt angle range	-5 - 20°
Display resolution *	2560 x 1440 pixels	On Screen Display (OSD)	✓
HD type *	Quad HD	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Native aspect ratio *	16:9	Plug and Play	✓
Display technology *	LED	LED indicators	Operation, Stand-by
Panel type *	VA		
Backlight type	W-LED		
Touchscreen *	✗		
Display brightness (typical)	250 cd/m ²		
Response time *	4 ms		
Anti-glare screen	✓		
Screen shape *	Flat		
Contrast ratio (typical) *	4000:1		
Dynamic contrast ratio marketing name	Mega Infinity DCR		
Maximum refresh rate *	75 Hz		
Viewing angle, horizontal	178°		
Viewing angle, vertical	178°		
Display number of colours *	16.7 million colours		
Pixel pitch	0.2331 x 0.2331 mm		
Pixel density	108.79 ppi		
Horizontal scan range	30 - 114 kHz		
Vertical scan range	48 - 75 Hz		
Viewable size, horizontal	59.7 cm		
Viewable size, vertical	33.6 cm		
Display diagonal (metric)	68.6 cm		
DDC/CI	✓		
Haze rate	25%		
Surface hardness	3H		
Colour gamut standard	sRGB		
		Power	
		Energy efficiency class (SDR) *	F
		Energy efficiency class (HDR) *	Not available
		Energy consumption (SDR) per 1000 hours *	26 kWh
		Power consumption (typical) *	25.2 W
		Power consumption (standby) *	0.5 W
		Power consumption (off)	0.3 W
		AC input voltage	100 - 240 V
		AC input frequency	50 - 60 Hz
		Power supply type	Internal
		Energy efficiency scale	A to G
		European Product Registry for Energy Labelling (EPREL) code	1258715
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Storage temperature (T-T)	-20 - 60 °C
		Operating relative humidity (H-H)	20 - 80%
		Operating altitude	0 - 3658 m
		Non-operating altitude	3658 - 12192 m

Display		Weight & dimensions	
Display sRGB	✓	Width (with stand)	614 mm
Performance		Depth (with stand)	231 mm
NVIDIA G-SYNC *	✗	Height (with stand)	458 mm
AMD FreeSync *	✗	Weight (with stand)	4.06 kg
VESA Adaptive Sync support	✓	Width (without stand)	614 mm
Component video sync	Separate sync	Depth (without stand)	53 mm
Flicker-free technology	✓	Height (without stand)	367 mm
Low Blue Light technology	✓	Weight (without stand)	3.61 kg
Multimedia		Packaging data	
Number of speakers	2	Package width	730 mm
RMS rated power	4 W	Package depth	141 mm
Built-in speaker(s) *	✓	Package height	453 mm
Built-in camera *	✗	Package weight	6.45 kg
Design		Packaging content	
Market positioning *	Home	Stand included	✓
Product colour *	Black	Cables included	HDMI, AC
Ports & interfaces		Manual	✓
Built-in USB hub *	✗	Sustainability	
HDMI *	✓	Sustainability compliance	✓
HDMI ports quantity	2	Doesn't contain	Mercury, PVC/BFR
HDMI version	1.4	Other features	
DisplayPorts quantity	1	Compatible operating systems	Mac OS X Windows 11 / 10 / 8.1 / 8 / 7
DisplayPort version	1.2	Exterior finish type	Textured
Audio output	✓	Picture enhancement	SmartImage
HDCP	✓	Recyclable packaging material	100%
HDCP version	1.4	Regulatory Approvals	CB; FCC Class B; ICES-003; CE Mark; CU-EAC; EAEU RoHS; TUV/ISO9241-307; TUV-BAUART
Ergonomics		EasyRead mode	✓
VESA mounting *	✓	LowBlue mode	✓
Panel mounting interface	100 x 100 mm	Compliance certificates	RoHS
Cable lock slot *	✓	Mean time between failures (MTBF)	50000 h
Cable lock slot type	Kensington		
Height adjustment *	✗		



8712581795108

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 04-NOV-2024. Prints or copies of Information are only valid on the printed Publication date