

ASUS ESD-T1A/BLK/G/AS// SSD enclosure Black M.2

Brand : ASUS

Product code: 90DD02N0-M09000

Product name : ESD-T1A/BLK/G/AS//

USB 3.2 de 2, 10 Gbps, 142 g

[ASUS ESD-T1A/BLK/G/AS// SSD enclosure Black M.2:](#)

Ultrafast performance: USB-C 3.2 Gen 2x1 interface for up to 10 Gbps transfer speeds, while SATA offers up to 6 Gbps

Dual M.2 interface: Supports M.2 NVMe PCIe or SATA SSDs with 2242/2260/2280 form factor

DIY-friendly design: Exclusive Q-latch mechanism makes it easy to mount an SSD into the enclosure

Military-grade toughness: Meets MIL-STD-810H drop resistance and IP68 water and dust resistance standards for added durability

Wide-ranging compatibility: Bundled USB-C cable to connect to PCs, laptops, mobile devices and the latest-gen gaming consoles

ASUS ESD-T1A/BLK/G/AS//. Product type: SSD enclosure. Number of storage drives supported: 1, Storage drive size: M.2, Supported storage drive interfaces: M.2, PCI Express, Serial ATA. Data transfer rate: 10 Gbit/s. Product colour: Black. USB connector type: USB Type-C



| | | | |
|--------------------------------------|------------------------------|-------------------------------------|-------------------------|
| Storage | | System requirements | |
| Number of storage drives supported * | 1 | Mobile operating systems supported | Android |
| Storage drive size * | M.2 | Windows operating systems supported | ✓ |
| Supported storage drive interfaces * | M.2, PCI Express, Serial ATA | Mac operating systems supported | ✓ |
| Ports & interfaces | | Operational conditions | |
| USB connectivity * | ✓ | Operating temperature (T-T) | 0 - 70 °C |
| USB version | 3.2 Gen 2 (3.1 Gen 2) | Storage temperature (T-T) | -40 - 60 °C |
| USB connector type | USB Type-C | Operating relative humidity (H-H) | 15 - 90% |
| USB connector gender | Female | Storage relative humidity (H-H) | 10 - 90% |
| Design | | Weight & dimensions | |
| Product type * | SSD enclosure | Width | 125.3 mm |
| Product colour * | Black | Depth | 54.3 mm |
| Key lock | ✓ | Height | 13.3 mm |
| Compatible products | PS5, Xbox | Weight | 142 g |
| Certification | MIL-STD-810H IP68 | Other features | |
| Performance | | Device type | Solid-state drive (SSD) |
| Data transfer rate | 10 Gbit/s | Logistics data | |
| Power | | Quantity per pack | 1 pc(s) |
| AC adapter output voltage | 5 V | | |



4711081826613

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 04-NOV-2024. Prints or copies of Information are only valid on the printed Publication date