

AOC V5 Q27V5CW/BK computer monitor 68.6 cm (27") 2560 x 1440 pixels Quad HD LED Black

Brand : AOC Product family: V5 Product code: Q27V5CW/BK

Product name: Q27V5CW/BK

Screen size (inch) 27, Panel resolution 2560x1440, Refresh rate 75 Hz, Response time MPRT 1 ms, Panel type IPS, USB-C connectivity USB-C 3.2×1 (DP alt mode, upstream, power delivery up to 65 W), HDMI HDMI 2.0×1 , Display Port DisplayPort 1.4×1 , D-SUB (VGA) 0x, DVI 0x, Sync technology (VRR) Freesync

AOC V5 Q27V5CW/BK computer monitor 68.6 cm (27") 2560 x 1440 pixels Quad HD LED Black:

${\bf 27}^{\prime\prime}$ IPS QHD model for extreme comfort and great viewing experience, with USB-C and Windows Hello integrated webcam

The AOC Q27V5CW is a 27" IPS panel with QHD resolution and ergonomic stand for not compromising on comfortable user experience and on outstanding picture quality. Boost your productivity with complete connectivity, including USB-C with Power Delivery up to 65W, 4 USB ports & HDMI, while also offering the extra security of a Windows Hello integrated webcam.







| Display | | Ports & interfaces | |
|---|---|---|--|
| Display diagonal * Display resolution * HD type * Native aspect ratio * Display technology * Panel type * Backlight type | 68.6 cm (27") 2560 x 1440 pixels Quad HD 16:9 LED IPS W-LED | Headphone out * Headphone outputs Headphone connectivity HDCP HDCP version AC (power) in Mobile High-Definition Link (MHL) | 1 3.5 mm 2.2 *** *** *** *** ** ** ** |
| Touchscreen * Display brightness (typical) | X 300 cd/m² | Ergonomics | |
| Response time * Anti-glare screen Screen shape * Contrast ratio (typical) * Contrast ratio (dynamic) Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours * Pixel pitch Pixel density | 300 cd/m ² 1 ms Flat 1000:1 20000000:1 75 Hz 178° 16.7 million colours 0.2331 x 0.2331 mm 109 ppi | VESA mounting * Panel mounting interface Wall mountable Cable lock slot * Cable lock slot type Height adjustment * Height adjustment Pivot Swivelling Tilt adjustment Tilt angle range LED indicators | 100 x 100 mm Kensington 13 cm 3.5 - 21.5° |
| Display diagonal (metric) Surface hardness | 68.6 cm 6H | Power | |
| sRGB coverage (typical) NTSC coverage (typical) Adobe RGB coverage DCI-P3 coverage | 123% 107% 105% 98% | Energy efficiency class (SDR) * Energy efficiency class (HDR) * Energy consumption (SDR) per 100 hours * | F G ⁰ 26 kWh |
| Performance | | Energy consumption (HDR) per 1000 hours * | 39 kWh |
| AMD FreeSync * AMD FreeSync type | √ FreeSync | Power consumption (typical) * Power consumption (standby) * | 40 W 0.5 W |

| Performance | | Power | |
|---|-------------------------------------|---|--|
| Fast charging Flicker-free technology Low Blue Light technology | ✓ ✓ ✓ ✓ | Power consumption (off) AC input voltage AC input frequency | 0.3 W 100 - 240 V 50 - 60 Hz |
| Multimedia | | Power supply type | Internal |
| Number of speakers RMS rated power Built-in speaker(s) * | 2 10 W | Energy efficiency scale European Product Registry for Energy Labelling (EPREL) code | A to G 1209390 |
| Built-in microphone | × | Weight & dimensions | |
| Built-in camera * | 7 | Width (with stand) | 613 mm |
| Design Market positioning * Home Product colour * Black Frameless design Front bezel colour Black | Home Black ✓ Black | Depth (with stand) Height (with stand) Weight (with stand) Width (without stand) Depth (without stand) Height (without stand) | 200 mm 516.6 mm 6.64 kg 613 mm 44.6 mm 363.4 mm |
| Detachable stand | √ | Packaging data | |
| Ports & interfaces Built-in USB hub * | Black | Package width Package depth | 840 mm 141 mm |
| USB hub version USB upstream port type | 3.2 Gen 1 (3.1 Gen 1) USB Type-C | Package height Package weight USB cable length | 456 mm 9.18 kg 1.8 m |
| Number of upstream ports Number of USB Type-C upstream | 1 | Packaging content | |
| ports quantity USB Type-A downstream ports quantity USB Type-C DisplayPort Alternate Mode | 1 4 • | Stand included Cables included HDMI cable length Power cable length | AC 1.5 m 1.5 m |
| USB Power Delivery | 1 | Other features | |
| USB Power Delivery up to | 65 W | Exterior finish type | Matt |
| DVI port HDMI * HDMI ports quantity | X ✓ 1 | Mean time between failures (MTBF) Light effects Certification | 50000 h X True |
| HDMI version DisplayPorts quantity DisplayPort version | 2.0 1 1.4 | | |



4038986180269

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.