

ASUS ZenWiFi AX (XT9) AX7800 1er Pack Schwarz Tri-band (2.4 GHz / 5 GHz / 5 GHz) Wi-Fi 6 (802.11ax) Black 4 Internal

Brand : ASUS

Product code: 90IG0740-MO3B50

Product name : ZenWiFi AX (XT9) AX7800 1er Pack Schwarz



ZenWiFi AX (XT9) AX7800 1er Pack, Black

ASUS ZenWiFi AX (XT9) AX7800 1er Pack Schwarz. Product colour: Black, Antenna type: Internal, Product type: Mesh system. Wi-Fi band: Tri-band (2.4 GHz / 5 GHz / 5 GHz), Top Wi-Fi standard: Wi-Fi 6 (802.11ax), Wi-Fi standards: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax). Processor frequency: 1.7 GHz, Internal memory: 512 MB, Flash memory: 256 MB. AC adapter input voltage: 110 - 240 V, AC adapter frequency: 50 - 60 Hz, AC adapter output voltage: 12 V. Weight: 740 g

Design		Wireless LAN features	
Product type	Mesh system	Instant Guard VPN Client L2TP VPN Client OVPN VPN Client PPTP VPN Client WireGuard VPN Server IPsec VPN Server OVPN VPN Server PPTP VPN Fusion VPN Server WireGuard	
Product colour *	Black	VPN support	
LED indicators	Power		
Antenna type *	Internal		
Antennas quantity	6		
Maximum coverage	264.77 m ²		
Reset button	✓		
Wireless LAN features		Features	
Wi-Fi band *	Tri-band (2.4 GHz / 5 GHz / 5 GHz)	Built-in processor	✓
Top Wi-Fi standard *	Wi-Fi 6 (802.11ax)	Processor cores	2
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Processor frequency	1.7 GHz
WLAN data transfer rate (first band)	574 Mbit/s	Internal memory	512 MB
WLAN data transfer rate (second band)	2402 Mbit/s	Flash memory	256 MB
WLAN data transfer rate (third band)	4804 Mbit/s	Quality of Service (QoS) support	✓
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11g, IEEE 802.11n	Parental control	✓
Security algorithms	WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK, WPA3-PSK, WPS	Parental control features	Custom profiles
IGMP snooping	✓	Firmware upgradeable via	Auto upgrade wizard
Dynamic DNS (DDNS)	✓	Operating modes	Wireless router mode, Access point mode
Guest access	✓	Ports & interfaces	
		Ethernet LAN (RJ-45) ports *	4
		Ethernet WAN	✓
		Power	
		AC adapter input voltage	110 - 240 V
		AC adapter frequency	50 - 60 Hz
		AC adapter output voltage	12 V
		AC adapter output current	3 A
		Weight & dimensions	
		Weight	740 g
		Packaging content	
		AC adapter included	✓
		Ethernet cable	✓



4711081743965

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 04-NOV-2024. Prints or copies of Information are only valid on the printed Publication date