

## Philips Brilliance 27B1U7903/00 LED display 68.6 cm (27") 3840 x 2160 pixels 4K Ultra HD Black

Brand : Philips

Product family: Brilliance

**Product code:** 27B1U7903/00

Product name : 27B1U7903/00

Professional Monitor 27B1U7903 4K UHD Mini-LED Thunderbolt™ 4 monitor

Philips Brilliance 27B1U7903/00 LED display 68.6 cm (27") 3840 x 2160 pixels 4K Ultra HD Black:

The Philips Thunderbolt <sup>™</sup> 4 monitor delivers a secure, reliable one-cable docking solution. Mini LED backlit and DisplayHDR <sup>™</sup> 1400 certified display generates outstanding picture performance and colour accuracy for colour-critical users.

Philips Brilliance 27B1U7903/00. Display diagonal: 68.6 cm (27"), Display resolution: 3840 x 2160 pixels, HD type: 4K Ultra HD, Display technology: LED, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black







## Display Ergonomics Display diagonal \* 68.6 cm (27") Height adjustment 13 cm Display resolution \* 3840 x 2160 pixels Pivot 1 4K Ultra HD Pivot angle -90 - 90° HD type \* Native aspect ratio \* 16:9 Swivelling 1 I FD -45 - 45° Display technology \* Swivel angle range Panel type \* IPS Tilt adjustment 1 Backlight type Mini LED Tilt angle range -5 - 15° On Screen Display (OSD) Touchscreen \* × 1 1400 cd/m<sup>2</sup> Display brightness (peak) Simplified Chinese, Traditional Chinese, Czech, German, Dutch, Display brightness (typical) 1000 cd/m<sup>2</sup> English, Spanish, Finnish, French, On Screen Display (OSD) languages Response time \* 4 ms Greek, Hungarian, Italian, Japanese, Anti-glare screen Korean, Polish, Portuguese, Russian, 1 Swedish, Turkish, Ukrainian Flat Screen shape \* Plug and Play 1 1300:1 Contrast ratio (typical) \* LED indicators Operation, Stand-by Dynamic contrast ratio marketing Mega Infinity DCR name Power Maximum refresh rate \* 60 Hz Energy efficiency class (SDR) \* G 178° Viewing angle, horizontal Energy efficiency class (HDR) \* G 178° Viewing angle, vertical Energy consumption (SDR) per 1000 65 kWh Display number of colours \* 1.07 billion colours hours Pixel pitch 0.1554 x 0.1554 mm Energy consumption (HDR) per 80 kWh Pixel density 163 ppi 1000 hours \* 30 - 140 kHz 74.5 W Horizontal scan range Power consumption (typical) \* 40 - 60 Hz 0.3 W Vertical scan range Power consumption (standby) \* Viewable size, horizontal 59.7 cm Power consumption (PowerSave) 45.1 W Viewable size, vertical 33.6 cm AC input voltage 100 - 240 V 50 - 60 Hz Display diagonal (metric) 68.6 cm AC input frequency High Dynamic Range (HDR) Power supply type Internal supported Energy efficiency scale A to G

| Display  |                       | Power  |   |
|--|-----------------------|--|---|
| High Dynamic Range (HDR)                       |                       | European Product Registry for                      | 1140000   |
| technology                                     | DisplayHDR 1400       | Energy Labelling (EPREL) code                      | 1140090   |
| DDC/CI   | 250/                  | Operational conditions                             |   |
| Haze rate<br>Surface hardness                  | 25%<br>3H             | Operating temperature (T-T)                        | 0 - 40 °C   |
| Colour gamut standard                          | sRGB                  | Storage temperature (T-T)                          | -20 - 60 °C   |
| sRGB coverage (typical)                        | 154%                  | Operating relative humidity (H-H)                  | 20 - 80%  |
| NTSC coverage (typical)                        | 121%                  | Operating altitude<br>Non-operating altitude       | 0 - 3658 m<br>3658 - 12192 m                          |
| Adobe RGB coverage                             | 99.2%                 | Weight & dimensions                                | 5555 12152 11   |
| DCI-P3 coverage<br>Display sRGB                | 97.2%                 | Width (with stand)                                 | 613 mm  |
|  | *                     | Depth (with stand)                                 | 204 mm  |
|  |                       | Height (with stand)                                | 515 mm  |
| NVIDIA G-SYNC *<br>AMD FreeSync *              | ×                     | Weight (with stand)                                | 9.43 kg   |
| Fast charging                                  | <b>^</b>              | Width (without stand)                              | 613 mm  |
| Fast charging technology                       | Power Delivery        | Depth (without stand)                              | 68 mm   |
| VESA Adaptive Sync support                     | ✓                     | Height (without stand)                             | 369 mm  |
| Component video sync                           | Separate sync         | Weight (without stand)                             | 7.02 kg   |
| Low Blue Light technology                      | √                     | Packaging data                                     | 705   |
| Multimedia                                     |                       | Package width                                      | 735 mm<br>285 mm                                      |
| Number of speakers                             | 2                     | Package depth<br>Package height                    | 423 mm  |
| RMS rated power                                | 6 W                   | Package weight                                     | 14.5 kg   |
| Built-in speaker(s) *                          | <u>_</u>              | Packaging content                                  | -   |
| Built-in camera *                              | ×                     | Stand included                                     | 1   |
| Design   |                       | Cables included                                    | AC, DisplayPort, HDMI                                 |
| Market positioning *                           | Office                | Manual   | 1   |
| Product colour *<br>Front bezel colour         | Black<br>Black        | Bundled software                                   | SmartControl  |
| Feet colour                                    | Black                 | Sustainability                                     |   |
| Ports & interfaces                             |                       | Sustainability compliance                          | ✓   |
| Built-in USB hub *                             | 4                     | Doesn't contain                                    | Mercury, PVC/BFR                                      |
| USB hub version                                | 3.2 Gen 1 (3.1 Gen 1) | Other features                                     |   |
| USB upstream port type                         | USB Type-C            | HBR3 support                                       | 1   |
| Number of upstream ports                       | 1                     | Compatible operating systems                       | Mac OS X Windows 10 / 8.1 / 8 / 7                     |
| USB Power Delivery<br>USB Power Delivery up to | ✓<br>90 W             | Picture-by-Picture (PbP)<br>Exterior finish type   | ✓<br>Textured   |
| HDMI *   | 30 W<br>✓             | Picture enhancement                                | SmartImage  |
| HDMI ports quantity                            | 2                     | Recyclable packaging material                      | 100%  |
| HDMI version                                   | 2.0                   |  | CB; CE Mark; FCC Class B; ICES-003;                   |
| DisplayPorts quantity                          | 1                     | Regulatory Approvals                               | cETLus; CU-EAC; EAEU RoHS;<br>SEMKO; TUV Ergo; TUV/GS |
| DisplayPort version                            | 1.4                   | Delta E  | 1   |
| Thunderbolt 4 ports quantity<br>Audio output   | 1                     | Light sensor                                       | ✓   |
| HDCP   | × ·                   | EasyRead mode                                      | ✓   |
| HDCP version                                   | 1.4/2.2               | LowBlue mode                                       |   |
| Network  |                       | Philips SmartUniformity<br>Compliance certificates | 93 - 105%<br>RoHS                                     |
| Ethernet LAN                                   | 1                     | Mean time between failures (MTBF)                  | 70000 h   |
| Ergonomics                                     |                       | Ethernet LAN data rates                            | 10,100,1000 Mbit/s                                    |
| VESA mounting *                                | 1                     | Wake-on-LAN  | 1   |
| Panel mounting interface                       | 100 x 100 mm          | Recycling data                                     |   |
| Cable lock slot *                              | <ul> <li>✓</li> </ul> | Post-consumer recycled plastic                     | 35%   |
|  | Kanalastas            | · ·  |   |
| Cable lock slot type                           | Kensington            |  |   |



8712581799632

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.