



Lindy 20m USB 3.0 Active Extension Pro

Brand : Lindy

Product code: 43361

Product name : 20m USB 3.0 Active Extension Pro

- High performance, active cable that provides an extended 20m connection between a computer and USB 3.0 device
- Can be used standalone or as part of the Lindy Active Extension System Pro to create bespoke extension systems of over 40m (depending on the cable configurations used)
- Supports the full USB 3.0 SuperSpeed bandwidth for speeds of 5Gbps
- Easy to use □ connects to the deviceandsquo;s existing USB cable (2m maximum)
- 2 year warranty

20m USB 3.0 Active Extension Pro

Lindy 20m USB 3.0 Active Extension Pro. Cable length: 20 m. Connector 1: USB A, Connector 2: USB A, USB version: USB 3.2 Gen 1 (3.1 Gen 1), Maximum data transfer rate: 5 Gbit/s, Connector contacts plating: Nickel, Product colour: Black, Magnetically shielded



| Features | | Features | |
|----------------------------|---------------------------|--------------------------------|--|
| USB version * | USB 3.2 Gen 1 (3.1 Gen 1) | | 0.064MHz - <0.08dB 0.256MHz - <0.11dB 0.512MHz - <0.13dB |
| Connector 1 * | USB A | | 0.772MHz - <0.15dB 1.0MHz - <0.20dB |
| Connector 2 * | USB A | | 4MHz - <0.39dB 8MHz - <0.57dB |
| Connector 1 gender * | Male | Nominal attenuation | 12MHz - <0.76dB 24MHz - <0.95dB |
| Connector 2 gender * | Female | | 48MHz - <1.35dB 96MHz - <1.90dB |
| Connector 1 form factor | Straight | | 200MHz - <3.20dB |
| Connector 2 form factor | Straight | | 400MHz - <5.80dB |
| Connector contacts plating | Nickel | Certification | CE, FCC, RoHS, REACH & California Proposition 65 |
| Magnetically shielded | ✓ | Weight & dimensions | |
| Cable jacket material | Polyvinyl chloride (PVC) | Cable length * | 20 m |
| Conductor material | Tinned copper | Weight | 1.6 kg |
| Maximum data transfer rate | 5000 Mbit/s | Packaging data | |
| Maximum data transfer rate | 5 Gbit/s | Package width | 230 mm |
| Product colour * | Black | Package depth | 198 mm |
| Cable type | Round cable | Package height | 120 mm |
| | | Package weight | 1.82 kg |
| | | Packaging content | |
| | | Quantity per pack * | 1 pc(s) |
| | | Operational conditions | |
| | | Operating temperature (T-T) | 0 - 50 °C |
| | | Storage temperature (T-T) | -20 - 60 °C |



4002888433617

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 04-NOV-2024. Prints or copies of Information are only valid on the printed Publication date