

Lindy 5m USB 3.2 Gen 2 C/C Active Extension

Brand: Lindy Product code: 43364

Product name: 5m USB 3.2 Gen 2 C/C Active Extension

- 5 metre USB 3.2 Active Extension Repeater Lead
- Supports transfer rates up to 10Gbps
- For even greater distances simply connect 2 cables in series
- Plug and Play
- 2 year warranty

5m USB 3.2 Gen 2 C/C Active Extension

Lindy 5m USB 3.2 Gen 2 C/C Active Extension. Cable length: 5 m. Connector 1: USB C, Connector 2: USB C, USB version: USB 3.2 Gen 2 (3.1 Gen 2), Maximum data transfer rate: 10 Gbit/s, Connector contacts plating: Nickel, Product colour: Black





Features		Features	
USB version * Connector 1 *	tor 1 * USB C USB C USB C Tor 1 gender * Male Tor 2 gender * Female Tor 1 form factor Tor 1 form factor Tor 2 form factor Tor 2 form factor Tor 3 form factor Tor 2 form factor Tor 3 form factor Tor 4 form factor Tor 5 fraight Tor 6 form factor Tor 6 form factor Tor 6 form factor Tor 7 form factor Tor 8 form factor Tor 8 form factor Tor 8 form factor Tor 8 form factor Tor 9 form factor Tor 9 form factor Tor 1 form factor Tor 1 form factor Tor 2 form factor Tor 3 form factor Tor 4 form factor Tor 4 form factor Tor 2 form factor Tor 3 form factor Tor 4 form factor Tor 4 form factor Tor 2 form factor Tor 3 form factor Tor 4 form factor Tor 4 form factor Tor 4 form factor Tor 4 form factor Tor 5 form factor Tor 4 form factor Tor 4 form factor Tor 5 form factor Tor 5 form factor Tor 6 form factor Tor 6 form factor Tor 7 form factor Tor 2 form factor Tor 2 form factor Tor 3 form factor Tor 4 form factor Tor 4 form factor Tor 5 form factor Tor 5 form factor Tor 5 form factor Tor 6 form factor Tor 7 form factor Tor 9 form factor To	Cable type Certification	Round cable CE, FCC, RoHS & REACH, CP65
Connector 2 * Connector 1 gender * Connector 2 gender * Connector 1 form factor Connector 2 form factor		Weight & dimensions Cable length * Cable diameter Weight	5 m 7 mm 320 g
Contact material Connector contacts plating Cable jacket material Conductor material		Packaging data Package type Package width Package depth Package weight	Polybag 236 mm 255 mm 350 g
Connector shielding Connector shield material Maximum data transfer rate Maximum data transfer rate Product colour *		Packaging content Quantity per pack * Operational conditions Operating temperature (T-T) Storage temperature (T-T)	1 pc(s) 0 - 50 °C -10 - 60 °C



4002888433648

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.