StarTech.com Lightning Car Charger with Coiled Cable, 1m Coiled Lightning Cable, 12W, White, 2 Port USB Car Charger Adapter for Phones and Tablets, Dual USB In Car iPhone Charger

Brand : StarTech.com

Product code: USBLT2PCARW2

Product name : Lightning Car Charger with Coiled Cable, 1m Coiled Lightning Cable, 12W, White, 2 Port USB Car Charger Adapter for Phones and Tablets, Dual USB In Car iPhone Charger


StarTech.com Lightning Car Charger with Coiled Cable, 1m Coiled Lightning Cable, 12W, White, 2 Port USB Car Charger Adapter for Phones and Tablets, Dual Device In Car iPhone Charger (USBLT2PCARW2) StarTech.com Lightning Car Charger with Coiled Cable, 1m Coiled Lightning Cable, 12W, White, 2 Port USB Car Charger Adapter for Phones and Tablets, Dual USB In Car iPhone Charger. Charger type: Auto, Power source type: Cigar lighter, Charger compatibility: Smartphone. Input voltage: 12 - 24 V, Maximum output voltage: 5 V. USB 2.0 ports quantity: 1. Cable length: 1 m, Product colour: White





CE

| Performance | | Packaging data | |
|--|--|---|--|
| Charger compatibility * Power source type * USB 2.0 ports quantity Lightning connector Charger type * Cable shielding | Smartphone Cigar lighter 1 ✓ Auto Aluminum mylar foil | Package width Package depth Package height Package weight | 110 mm 130 mm 50 mm 7.2 g |
| | | Operational conditions | |
| Design Product colour * | White | Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) | 0 - 40 °C -25 - 70 °C 8 - 90% |
| Cable length | 1 m | Technical details | |
| Power nput voltage 12 - 24 V | 12 - 24 V | Sustainability compliance Compliance certificates | ✓ CE |
| Input current | 3 A | Logistics data | |
| Maximum power Maximum output voltage Port 1 output current Port 2 output current Output current | 12 W 5 V 2.1 A 2.1 A 4200 mA | Master (outer) case width Master (outer) case length Master (outer) case height Products per master (outer) case | 405 mm 435 mm 355 mm 60 pc(s) |
| Weight & dimensions | | Other features | |
| Width Depth Height Weight | 28 mm 471 mm 36 mm 6 g | Cable jacket material Connector contacts plating | Polyvinyl chloride (PVC) Nickel |





065030883757

0065030883757

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.