

## **DELL E Series 24 Monitor - E2424HS**

Brand : DELL Product family: E Series Product code: DELL-E2424HS

Product name: 24 Monitor -

E2424HS

- 60.5cm (23.8") Full HD 1920 x 1080 LED VA
- 8ms, 16:9, 3000:1
- VGA, HDMI, DisplayPort

60.5cm (23.8") Full HD 1920 x 1080 LED VA, 16:9, 16.7M, 8ms, 178°/178°, 3000:1

## DELL E Series 24 Monitor - E2424HS:

Get outstanding value with this 23.8-inch FHD monitor featuring new three-sided narrow bezel, height adjustable stand with DP, HDMI and VGA ports.

DELL E Series 24 Monitor - E2424HS. Display diagonal: 60.5 cm (23.8"), Display resolution:  $1920 \times 1080$  pixels, HD type: Full HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal:  $178^\circ$ , Viewing angle, vertical:  $178^\circ$ . Built-in speaker(s). VESA mounting, Height adjustment. Product colour: Black











Display		Ergonomics	
Display diagonal * Display resolution * HD type *	60.5 cm (23.8") 1920 x 1080 pixels Full HD	On Screen Display (OSD) Plug and Play LED indicators	1 1 1
Native aspect ratio * Display technology * Panel type * Backlight type Touchscreen * Display brightness (typical) Response time * Anti-glare screen Screen shape * Contrast ratio (typical) * Maximum refresh rate *	tot ratio *  tot	Power  Energy efficiency class (SDR) * Energy efficiency class (HDR) * Energy consumption (SDR) per 1000 hours * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (off) AC input voltage AC input frequency	D Not available 14 kWh 16 W 0.3 W 28 W 0.3 W 100 - 240 V 50 - 60 Hz
Viewing angle, horizontal Viewing angle, vertical Display number of colours * Response time (fast) Pixel pitch Pixel density		Input current Power supply type Energy efficiency scale European Product Registry for Energy Labelling (EPREL) code	1.5 A Internal A to G 1294066
Viewable size, horizontal Viewable size, vertical Digital horizontal frequency Digital vertical frequency Display diagonal (metric) High Dynamic Range (HDR) supported		Operational conditions  Operating temperature (T-T)  Storage temperature (T-T)  Operating relative humidity (H-H)  Storage relative humidity (H-H)  Operating altitude  Non-operating altitude	0 - 40 °C -20 - 60 °C 10 - 80% 5 - 90% 0 - 5000 m 5000 - 12192 m
Colour gamut standard Colour gamut	NTSC 83%	Weight & dimensions Width (with stand)	538.6 mm

Performance		Weight & dimensions	
NVIDIA G-SYNC *  AMD FreeSync *  Flicker-free technology  Low Blue Light technology	× × √	Depth (with stand) Height (with stand) Weight (with stand) Width (without stand)	209.5 mm 512.1 mm 4.06 kg 538.6 mm
Multimedia		Depth (without stand)	48.9 mm
Number of speakers RMS rated power Built-in speaker(s) * Built-in camera *	2 2 W ✓	Height (without stand) Weight (without stand) Bezel width (side) Bezel width (top) Bezel width (bottom)	324.2 mm 2.82 kg 5.8 mm 5.8 mm 2.19 cm
Design		Packaging data	2.25 0
Market positioning *	Office	Package weight	5.96 kg
Product colour *	Black	5 5	3.30 kg
Front bezel colour  Detachable stand	Black ✓	Packaging content Stand included	<b>√</b>
Feet colour	Black	Cables included	AC, HDMI
Ports & interfaces		Quick start guide	<b>√</b>
Built-in USB hub *	×	Sustainability	
VGA (D-Sub) ports quantity	1	Sustainability certificates	ENERGY STAR, TCO
HDMI*	<u> </u>	Doesn't contain	PVC/BFR
HDMI ports quantity	1	Carbon footprint	
DisplayPorts quantity	1	Total carbon footprint (kg of CO2e)	466
DisplayPort version	1.2	Total carbon emissions, standard	131
Headphone out *  AC (power) in	×	deviation (kg of CO2e)	131
Network	•	Carbon emissions, manufacturing (kg of CO2e)	299
Wi-Fi	×	Carbon emissions, logistics (kg of CO2e)	27
Ergonomics	,	Carbon emissions, energy usage (kg of CO2e)	136
VESA mounting * Panel mounting interface	100 x 100 mm	Carbon emissions, end-of-life (kg of CO2e)	3
Cable management Cable lock slot *	1	Total carbon emissions, w/o use phase (kg of CO2e)	330
Cable lock slot type	Kensington	PAIA version	1.3.2
Height adjustment *	<b>√</b>	Other features	
Height adjustment Pivot	13 cm	Heavy metals free	Hg (mercury)
Swivelling	×	Compliance certificates	RoHS
Swivel angle range	-173 - 173°		
Tilt adjustment	<b>√</b>		



5397184657089

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.