



## GIGABYTE GP-UD1000GM PG5 V2 power supply unit 1000 W 20+4 pin ATX ATX Black

**Brand :** GIGABYTE


**Product code:** GP-UD1000GM PG5 V2

**Product name :** GP-UD1000GM PG5 V2

- Main Japanese capacitors
- Enhanced thermal solution
- 120mm smart hydraulic bearing (HYB) fan
- OVP/OPP/SCP/UVF/OCP/OTP protection
- Support PCIe Gen 5.0 graphics card
- High-quality native 16-pin cable supports 600W output
- 80 PLUS Gold certified
- Fully modular design
- Compact design

1000 W, Fan Size 120 mm, Intel ATX 12 V, 80 PLUS Gold, Black

GIGABYTE GP-UD1000GM PG5 V2. Total power: 1000 W, AC input voltage: 100 - 240 V, AC input frequency: 50 - 60 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 61 cm, SATA power cable length: 150,600 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Width: 150 mm, Depth: 86 mm, Height: 140 mm



Power		Ports & interfaces	
Total power *	1000 W	PCI Express power cable length	70 cm
AC input voltage *	100 - 240 V	CPU power connector (4+4 pin)	✓
AC input frequency	50 - 60 Hz	CPU power cable length	80 cm
Input current	6.5 - 15 A	ATX power connector (20+4 pin)	✓
Power Factor Correction (PFC) type	Active	Cabling type	Fully-Modular
Hold time	16 ms	Performance	
Efficiency	90%	80 PLUS certification *	80 PLUS Gold
Power protection features	Over current, Over power, Over voltage, Short circuit, Under voltage	Purpose *	PC
Ports & interfaces		Power supply unit (PSU) form factor *	ATX
Motherboard power connector *	20+4 pin ATX	Bearing technology	HYB
Motherboard power cable length	61 cm	Mean time between failures (MTBF)	100000 h
Number of SATA power connectors	8	Design	
SATA power cable length	150,600 mm	Product colour	Black
Peripheral (Molex) power connectors (4-pin) *	4	Cooling type	Active
Peripheral (Molex) power cable length	120,150,500 mm	Fan diameter	12 cm
PCI Express power connectors (6+2 pin)	4	Weight & dimensions	
PCI Express power connectors (16-pin)	1	Width	150 mm
		Depth	86 mm
		Height	140 mm

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 04-NOV-2024. Prints or copies of Information are only valid on the printed Publication date