



Origin Storage 3TB 7.2k PowerEdge R/T x10 Series 3.5in Near Line SAS Hotswap HD w/ Caddy SHIPS AS 4TB

Brand : Origin Storage

Product code: DELL-3000NLS/7-S11

Product name : 3TB 7.2k PowerEdge R/T x10 Series 3.5in Near Line SAS Hotswap HD w/ Caddy SHIPS AS 4TB

- Does not invalidate OEM warranty
 - 100% compatible replacement/upgrade for storage solutions
 - Pre- & Post-Sale UK Based Tech Support
- 3TB 7.2k PowerEdge R/T x10 Series 3.5in Near Line SAS Hotswap HD w/ Caddy SHIPS AS 4TB



Origin Storage 3TB 7.2k PowerEdge R/T x10 Series 3.5in Near Line SAS Hotswap HD w/ Caddy SHIPS AS 4TB:



Origin Storage Ltd manufactures a full range of Matched Hard Drive & Solid State Solutions for most major branded Servers, laptops and desktops, such as Dell, HP, Toshiba, and Lenovo. All of our Matched Drive Solutions come with up to 5 years advanced replacement warranty and also come with free pre and post sales technical support. We can supply replacements or upgrades in form factors of 2.5" or 3.5" with either SATA or SAS interfaces, available in a range of capacities and spin speeds. All our Matched Drive Solutions are just that, matched to the system you have for 100% compatibility, right first time, every time!

Features		Operational conditions	
HDD capacity *	4 TB	Operating relative humidity (H-H)	5 - 95%
HDD speed *	7200 RPM	Storage relative humidity (H-H)	5 - 95%
Storage drive buffer size *	128 MB	Operating vibration	0.5 G
HDD size *	3.5"	Non-operating vibration	0.25 G
Interface *	SAS	Operating altitude	-304.8 - 3048 m
Type *	HDD	Non-operating altitude	-304.8 - 12192 m
Component for *	Server/workstation	Operating shock	70 G
Hot-swap *	✓	Non-operating shock	300 G
HDD interface transfer rate	12 Gbit/s	Packaging content	
Average latency	4.16 ms	Storage drive adapter included	✗
Bytes per sector	512	Weight & dimensions	
Mean time between failures (MTBF)	2000000 h	Width	101.8 mm
Refurbished	✗	Height	26.1 mm
Power		Depth	147 mm
Power consumption (typical)	10.72 W	Weight	850 g
Power consumption (idle)	6.74 W	Logistics data	
Operating voltage	5 / 12 V	Harmonized System (HS) code	84717050
Operational conditions		Other features	
Operating temperature (T-T)	5 - 55 °C	Compliance certificates	RoHS
Storage temperature (T-T)	-40 - 70 °C		



5055146573586



5054484202950

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.