



## Lexmark XC2132 BK toner cartridge 1 pc(s) Original Black

**Brand :** Lexmark

**Product code:** 24B6011

**Product name :** XC2132 BK

XC2132 Black Standard Yield Cartridge, 6000 pages

[Lexmark XC2132 BK toner cartridge 1 pc\(s\) Original Black:](#)



### Unison™ Toner

Essential to Lexmark print system performance, Unison™ Toner's unique formulation consistently delivers outstanding image quality, ensures long-life print system reliability and promotes superior sustainability -- all in an innovative shake-free print system.

### Best Together

Genuine Lexmark supplies are engineered to work Best Together with your Lexmark printer, delivering excellent print quality from the first page to the last.

### Lexmark Cartridge Collection Programme

Going green has never been easier. Recycle all your used Lexmark supplies by letting us take care of the details. It's simple, smart and always free.

Lexmark XC2132 BK. Black toner page yield: 6000 pages, Printing colours: Black, Quantity per pack: 1 pc(s)

| Features                     |                | Operational conditions            |                |
|------------------------------|----------------|-----------------------------------|----------------|
| Compatibility *              | Lexmark XC2132 | Operating relative humidity (H-H) | 20 - 80%       |
| Quantity per pack *          | 1 pc(s)        | Storage temperature (T-T)         | -20 - 40 °C    |
| Cartridge capacity           | Standard Yield | Storage relative humidity (H-H)   | 10 - 60%       |
| Black toner page yield *     | 6000 pages     | Other features                    |                |
| Type *                       | Original       | Print technology                  | Laser printing |
| Printing colours *           | Black          | Page yield footnote               | ISO/IEC 19752  |
| Printing material shelf life | 2 year(s)      | Logistics data                    |                |
| Product colour               | Black          | Harmonized System (HS) code       | 84439990       |
| Operational conditions       |                |                                   |                |
| Operating temperature (T-T)  | 10 - 40 °C     |                                   |                |



0734646498777



734646498777

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.