

Chief PF1UB monitor mount / stand 190.5 cm (75") Floor Black

Brand : Chief Product code: PF1UB

Product name: PF1UB

- Centris Technology provides effortless, fingertip tilt
- Screen angle stays set in place until you decide to re-adjust
- Provides telescoping height adjustment without tools
- ClickConnect Technology provides an audible click to confirm that the flat panel is locked in place
- Offers quick connect/disconnect wtih no tools necessary
- Includes integrated security with the addition of a padlock
- Screen can be installed in portrait or landscape orientation (PAC400 accessory can be used to rotate without removing the screen)
- Integrated cable management with flexible covers to hide cables out of sight for a fast, clean installation $\frac{1}{2} \left(\frac{1}{2} \right) = \frac{1}{2} \left(\frac{1}{2} \right) \left(\frac{1}{2}$
- Flat, angled base makes corner positioning easy

Flat Panel 4' - 7' Floor Stand (up to 65")

Chief PF1UB monitor mount / stand 190.5 cm (75") Floor Black:

A solid, low-profile solution for mounting a flat panel on a floor AV stand.

- Ideal for digital signage and corporate presentations
- PF1UB and PF1US ship with a universal interface bracket
- PF12000B and PF12000S require a PSB interface to be purchased separately





| Mounting | | Design | |
|---|---|-------------------------------|---------------------------|
| Minimum screen size * 106.7 cm (42") Maximum weight capacity * 90.7 kg Maximum screen size * 190.5 cm (75") | Housing material Product colour * Base type | Steel Black Floor plate | |
| Suitable for TV | Floor 200 x 200 mm 800 x 400 mm 200 x 200,300 x 300,400 x 200,400 | Weight & dimensions | |
| Mounting type * Minimum VESA mount * Maximum VESA mount * | | Width Depth Weight | 914 mm 762 mm 65 kg |
| Panel mounting interface | x 400,600 x 400,700 x 400,800 x 400 | Packaging data | |
| Number of displays supported * | 1 | Package weight | 65.3 kg |
| Ergonomics | | Packaging content | |
| Height adjustment | 1 | Mounting kit | ✓ |
| Height adjustment range | 1300 - 2100 mm | Other features | |
| Tilt adjustment Tilt angle range | √ -15 - 15° | Height (max) Adjustable | 2.39 m ✓ |
| Cable management | V | Logistics data | |
| Telescopic | √ | Harmonized System (HS) code | 85299097 |





841872100654

0841872100654

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.