



## ATEN VE802R-AT-E AV extender AV receiver Black

**Brand :** ATEN

**Product code:** VE802R-AT-E

**Product name :** VE802R-AT-E



Receiver, 4096 x 2160, HDMI, RS-232, CEC, HDCP, 460 g

**ATEN VE802R-AT-E AV extender AV receiver Black:**

The VE802R HDMI HDBaseT-Lite Receiver connects with HDBaseT transmitters\* to extend signals up to 70m from the source using one Cat 5e/6/6a cable. It supports RS-232 and IR signaling pass-through, allowing you to control the HDMI source device from the remote unit (VE802R) while also granting access to the HDMI display device from the local unit (VE802T). IR signals can also be extended in both directions. The VE802R is HDMI (3D, Deep Color,4k) and HDCP compatible. The VE802R is perfect for a digital entertainment center or any installation that requires superior video quality.



Compatible HDBaseT Transmitter Units: VE802T

ATEN VE802R-AT-E. Type: AV receiver, Maximum resolution: 4096 x 2160 pixels, Cable types supported: Cat5, Cat6, Cat6a. Connectivity technology: Wired. AC input frequency: 60 Hz, Operating voltage: 5 V, Power consumption (receiver) (max): 4 W. Receiver dimensions (WxDxH): 123 x 144.8 x 30 mm, Receiver weight: 460 g

Features		Ports & interfaces	
Type *	AV receiver	Audio input	1
Maximum resolution *	4096 x 2160 pixels	Audio output	1
Cable types supported	Cat5, Cat6, Cat6a	Remote (IR) output	1
Maximum transfer distance	70 m	DC-in jack	✓
Supported video modes	2160i	<b>Power</b>	
Supported graphics resolutions	4096 x 2160	AC input frequency	60 Hz
Bandwidth	340 MHz	Operating voltage	5 V
HDCP	✓	Power consumption (receiver) (max)	4 W
Material	Metal	<b>Operational conditions</b>	
Consumer Electronics Control (CEC) support	✓	Operating temperature (T-T)	0 - 50 °C
Impedance	100 Ω	Storage temperature (T-T)	-20 - 60 °C
Product colour	Black	Operating relative humidity (H-H)	0 - 80%
Ports & interfaces		Weight & dimensions	
Connectivity technology *	Wired	Receiver dimensions (WxDxH)	123 x 144.8 x 30 mm
HDMI in	1	Receiver weight	460 g
Number of HDMI outputs	1	<b>Packaging content</b>	
RS-232 output ports	1	Manual	✓
		IR receiver included	✓

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 04-NOV-2024. Prints or copies of Information are only valid on the printed Publication date