



CyberPower BR700ELCD uninterruptible power supply (UPS) Line-Interactive 0.7 kVA 420 W 6 AC outlet(s)

Brand : CyberPower

Product code: BR700ELCD-UK

Product name : BR700ELCD

Line-Interactive, 700VA/420W, AVR, LCD

[CyberPower BR700ELCD uninterruptible power supply \(UPS\) Line-Interactive 0.7 kVA 420 W 6 AC outlet\(s\):](#)

CyberPower BR700ELCD offers home and office users a reliable battery backup and safeguards office PCs, network communication equipment, and other electronic devices from surges, spikes, brownouts and other power incidents. Designed with GreenPower UPS™ Technology to improve operating efficiency and to minimize energy consumption, users can enjoy significant energy cost savings over conventional UPS systems.

The UPS provides Automatic Voltage Regulation (AVR) to maintain a safe voltage for connected equipment. The featured data line protection protects phones, networks, and other communication equipment against surge/spikes and other power irregularities. Users can access precise information of critical power/battery conditions by switching to the LCD status monitor.



Features		Battery	
UPS topology *	Line-Interactive	Typical backup time at full load	2 min
Output power capacity *	0.7 kVA	Typical backup time at half load	6 min
Output power *	420 W	Battery recharge time	8 h
Waveform *	Sine	Cold start	✓
Input operation voltage (min) *	165 V	Design	
Input operation voltage (max) *	290 V	Form factor *	Compact
Input frequency *	50/60 Hz	Housing material	Plastic
Output frequency	50/60 Hz	Product colour *	Black
Automatic Voltage Regulation (AVR)	✓	Display type	LCD
Surge energy rating	125 J	LED indicators	✓
Response time	4 ms	Certification	CE RoHS
EMI/RFI noise filtering	✓	Operational conditions	
Surge protection	✓	Operating temperature (T-T)	0 - 40 °C
Surge protection features	Digital Subscriber Line (DSL), Fax, Modem, Network, Telephone	Storage temperature (T-T)	-20 - 50 °C
Power protection features	Overload	Operating relative humidity (H-H)	0 - 90%
Audible alarm(s)	✓	Storage relative humidity (H-H)	0 - 90%
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm	Operating altitude	0 - 3000 m
Ports & interfaces		Weight & dimensions	
AC outlets quantity	6 AC outlet(s)	Width	166 mm
USB port	✓	Depth	288 mm
USB 2.0 ports quantity	1	Height	118 mm
Serial interface	✗	Weight	5.3 kg
Modem (RJ-11) ports	2	Packaging data	
Ethernet LAN (RJ-45) ports	2	Bundled software	PowerPanel® Personal Edition
Battery		Other features	
Battery technology	Sealed Lead Acid (VRLA)	Nominal output voltage	230 V

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 04-NOV-2024. Prints or copies of Information are only valid on the printed Publication date