

Epson WorkForce DS-80W

Brand : Epson

Product family: WorkForce

Product code: B11B253402

Product name : WorkForce DS-80W



- Scan anywhere: Small, lightweight design
- USB cable or integrated battery power: Scan up to 300 pages between battery charges
- Fast scanning speeds: At up to four seconds per page (8.5ppm)
- Simplify your workload: Continuous scanning with automatic feed mode
- Includes a range of software: Document Capture Pro 2, Epson Scan 2.0 and TWAIN driver support

WorkForce DS-80W
Epson WorkForce DS-80W. Maximum scan size: 216 x 1828 mm, Optical scanning resolution: 600 x 600 DPI, Input colour depth: 48 bit. Scanner type: Handheld scanner, Product colour: White, Display: LCD. Sensor type: CIS, Daily duty cycle (max): 300 pages, Light source: ReadyScan LED. Auto document feeder (ADF) input capacity: 1 sheets. Maximum ISO A-series paper size: A4, Scanning media types supported: Business Card, Plastic Card, Post Card(JPN), Paper tray media weight: 35 - 270 g/m²

Scanning		Packaging data	
Maximum scan size *	216 x 1828 mm	Package weight	597 g
Optical scanning resolution *	600 x 600 DPI	System requirements	
Colour scanning	✓	Compatible operating systems	Mac OS 10.6+, Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Server 2003, Windows Server 2008 (32/64 Bit), Windows Server 2012 R2, Windows Server 2016, Windows Vista, Windows XP
Duplex scanning *	✗		
Input colour depth	48 bit	Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Vista, Windows XP
Output colour depth	24 bit		
Input greyscale depth	16 bit	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Output greyscale depth	8 bit		
Output monochrome depth	8 bit	Server operating systems supported	Windows Server 2003, Windows Server 2008, Windows Server 2008 x64, Windows Server 2012 R2, Windows Server 2016
Scan speed (b/w, low res, A4)	4 sec/page		
Scan speed (colour, low res, A4)	4 sec/page	Operational conditions	
Design		Operating temperature (T-T)	5 - 35 °C
Scanner type *	Handheld scanner	Storage temperature (T-T)	-25 - 60 °C
Product colour *	White	Operating relative humidity (H-H)	10 - 85%
Display	LCD	Storage relative humidity (H-H)	10 - 90%
Colour display	✗	Weight & dimensions	
Built-in display *	✓	Width	272 mm
Performance		Depth	47 mm
Sensor type *	CIS	Height	34 mm
Light source	ReadyScan LED	Weight	300 g
Scan file formats	BMP, JPEG, PDF, PNG, TIFF	Packaging content	
Daily duty cycle (max) *	300 pages	Cables included	USB
Scan drivers	TWAIN, WIA, SANE, ICA	Bundled software	Document Capture Pro 2.0, Epson Scan 2
Input capacity		Other features	
Auto document feeder (ADF) input capacity	1 sheets	Output resolutions	600 dpi
Paper handling		Image formats supported	BMP, JPEG, TIFF, PNG
Scanning media types supported	Business Card, Plastic Card, Post Card(JPN)		
Maximum ISO A-series paper size *	A4		
Paper tray media weight	35 - 270 g/m ²		
Auto Document Feeder (ADF) media weight	35 - 270 g/m ²		
Ports & interfaces			
USB port *	✓		
USB version	2.0		

Ports & interfaces		Technical details	
Standard interfaces	USB 2.0, Wireless LAN	Master (outer) case GTIN (EAN/UPC) 8715946663005	
Power		Logistics data	
Power supply type *	USB	Products per pallet	360 pc(s)
Network		Master (outer) case length	360 mm
Wi-Fi	✓	Master (outer) case height	320 mm
Features		Master (outer) case width	350 mm
Country of origin	China	Pallet gross length	120 cm
Packaging data		Pallet gross width	80 cm
Quantity per pack	1 pc(s)	Pallet gross height	171 cm
Package width	141 mm	Products per master (outer) case	10 pc(s)
Package depth	330 mm	Products per pallet layer	60 pc(s)
Package height	67 mm	Products per pallet layer (UK)	60 pc(s)
		Products per pallet (UK)	360 pc(s)
		Pallet length (UK)	120 cm
		Pallet width (UK)	100 cm
		Pallet height (UK)	171 cm
		Harmonized System (HS) code	84716070



8715946662848

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 04-NOV-2024. Prints or copies of Information are only valid on the printed Publication date