

ZYXEL

Zyxel XGS1930-28HP Managed L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Brand : Zyxel

Product code: XGS1930-28HP-GB0101F

Product name : XGS1930-28HP



- IEEE 802.3 10BASE-T Ethernet
- IEEE 802.3u 100BASE-TX Ethernet
- IEEE 802.3ab 1000BASE-T Ethernet
- IEEE 802.3z 1000BASE-X
- IEEE 802.3ae 10-Gigabit Ethernet Over Fiber
- IEEE 802.3af PoE
- IEEE 802.3at PoE Plus
- IEEE 802.3az EEE
- IEEE 802.3x flow control
- IEEE 802.3ad LACP aggregation
- IEEE 802.1D Spanning Tree Protocol (STP)
- IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)
- IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
- IEEE 802.1p Class of Service (CoS) prioritization
- IEEE 802.1X port authentication

XGS1930-28HP - 24-port GbE Smart Managed PoE Switch with 4 SFP+ Uplink

Zyxel XGS1930-28HP. Switch type: Managed, Switch layer: L3. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24. MAC address table: 16000 entries, Switching capacity: 128 Gbit/s. Networking standards: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE.... Power over Ethernet (PoE). Rack mounting



Management features		Design	
Switch type *	Managed	Rack mounting *	✓
Switch layer	L3	Product colour	Black
Quality of Service (QoS) support	✓	Electromagnetic compatibility	FCC 15 A, CE A, BSMI EMC
Web-based management	✓	Performance	
Ports & interfaces		Internal memory	512 MB
Basic switching RJ-45 Ethernet ports quantity *	24	Flash memory	32 MB
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Noise level	28.5 dB
SFP+ module slots quantity	4	Mean time between failures (MTBF)	1369432 h
Network		Power	
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	AC input voltage	100 - 240 V
Port mirroring	✓	AC input frequency	50 - 60 Hz
IP routing	✓	Power consumption (max)	471 W
Routing entries	32	Power over Ethernet (PoE)	
Flow control support	✓	Power over Ethernet (PoE) *	✓
Link aggregation	✓	Power over Ethernet (PoE) ports quantity	24
Broadcast storm control	✓	Total Power over Ethernet (PoE) budget	375 W
Spanning tree protocol	✓	Operational conditions	
VLAN support	✓	Operating temperature (T-T)	0 - 50 °C
Virtual LAN features	Port-based VLAN, Voice VLAN	Storage temperature (T-T)	-40 - 70 °C
Number of VLANs	4000	Operating relative humidity (H-H)	10 - 95%
Data transmission		Storage relative humidity (H-H)	10 - 95%
Switching capacity *	128 Gbit/s	Heat dissipation	1606.11 BTU/h
Forwarding rate	95.2 Mpps	Weight & dimensions	
MAC address table *	16000 entries	Width	441 mm
Static route	✓	Depth	330 mm
		Height	44 mm
		Weight	4.6 kg

Data transmission		Packaging content	
Packet buffer memory	1.5 MB	Cables included	AC
Security		Rack mount kit	✓
DHCP features	DHCP client, DHCP relay, DHCPv6 relay	Packaging data	
Access Control List (ACL)	✓	Package type	Box
IGMP snooping	✓	Package width	585 mm
SSH/SSL support	✓	Package depth	503 mm
Loop protection	✓	Package height	95 mm
Authentication	Guest VLAN, MAC-based authentication, Port-based authentication	Package weight	5.82 kg
Password protection	✓	Logistics data	
Multicast features		Harmonized System (HS) code	85176990
Multicast support	✓		
Protocols			
GARP VLAN Registration Protocol (GVRP)	✓		



4718937595013

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 04-NOV-2024. Prints or copies of Information are only valid on the printed Publication date