

BenQ InstaShow WDC10C wireless presentation system USB Type-C

Brand : BenQ Product code: 9H.JLD78.N3E

Product name : InstaShow WDC10C

IEEE 802.11ac 5GHz, AES 128 bit, 1080p, HDMI 1.4 (HDCP), USB Type-C BenQ InstaShow WDC10C. Product colour: Black. Supported graphics resolutions: 800×600 (SVGA), 1024×768 (XGA), 1280×1024 (SXGA), 1280×720 (HD 720), 1280×768 , $1280 \times ...$, Supported video modes: 720p, 1080p, Maximum frame rate: 60 fps. Antenna type: Internal & external. Wi-Fi standards: Wi-Fi 5 (802.11ac), Wi-Fi data rate (max): 867 Mbit/s, Top Wi-Fi standard: Wi-Fi 5 (802.11ac). Interface: USB Type-C





Design		Power	
Product colour	Black	Power source type *	DC, USB
LED indicators	✓	Input voltage	5 V
Features		System requirements	
Supported graphics resolutions	800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 768, 1280 x 800, 1280 x 960, 1360 x 768 (WXGA), 1400 x 1050 (SXGA+), 1440 x 900 (WXGA+), 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080)	Windows operating systems supported Mac compatibility Mac operating systems supported	✓ ✓
		Operational conditions	
Supported video modes	720p, 1080p	Operating temperature (T-T)	0 - 40 °C
Maximum frame rate	60 fps	Operating relative humidity (H-H)	10 - 80%
Concurrent users	16 user(s)	Storage temperature (T-T)	-10 - 60 °C
Security updates end date	31/12/2024	Storage relative humidity (H-H)	5 - 90%
Management features		Weight & dimensions	
Reset button	✓	Weight	1.27 kg
Antenna		Package width	390 mm
Antenna type	Internal & external	Package depth Package height	485 mm 205 mm
Network		Package weight	7.6 kg
Wi-Fi standards	Wi-Fi 5 (802.11ac)	Packaging content	,
Wi-Fi data rate (max)	867 Mbit/s		LIDMI LICE
Top Wi-Fi standard	Wi-Fi 5 (802.11ac)	Cables included Quick start guide	HDMI, USB ✓
Frequency band	5 GHz	· J	•
Ethernet LAN	✓	Logistics data	
Ethernet LAN data rates	10,100 Mbit/s	Country of origin	Taiwan
Security algorithms	128-bit AES, WPA2, WPA2- Enterprise, WPA2-PSK	Products per pallet Harmonized System (HS) code	144 pc(s) 8517620000
Maximum operating distance	8 m		
Ports & interfaces			
Interface *	USB Type-C		
Number of HDMI outputs	1		
HDMI version	1.4		

Ports & interfaces

Ethernet LAN (RJ-45) ports 1
DC-in jack ✓





4718755078804

0840046041380



840046041380

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.