## ASUS ZenWiFi AX (XT8) wireless router Gigabit Ethernet Tri-band (2.4 GHz / 5 GHz / 5 GHz) White

**Brand**: ASUS **Product code**: 90IG0590-M03G40

Product name: ZenWiFi AX (XT8)

ZenWiFi AX (XT8), 802.11a/b/g/n/ac/ax, 2.4 + 5 GHz, 512 MB RAM, RJ-45, USB 3.1, MU-MIMO, 160x75x161.5 mm, white, 2 pcs

ASUS ZenWiFi AX (XT8). WAN connection type: RJ-45. Wi-Fi band: Tri-band (2.4 GHz / 5 GHz / 5 GHz), Top Wi-Fi standard: Wi-Fi 6 (802.11ax), WLAN data transfer rate (max): 6600 Mbit/s. Ethernet LAN interface type: Gigabit Ethernet, Ethernet LAN data rates: 1000 Mbit/s, Networking standards: IEEE 802.11a, IEEE 802.11a, IEEE 802.11b, IEEE 802.11p, IEEE 802.11n. Security algorithms: WPA-Enterprise, WPA-PSK, WPA-PSK, WPA-PSK, WPA-PSK, WPS, NAT functionality: PPTP, L2TP, IPSec, RTSP, H.323, SIP, PPPoE. Product type: Tabletop router, Product colour: White





WAN connection		Security	
Ethernet WAN * DSL WAN * SIM card slot * WAN connection type	✓ <b>×</b> <b>×</b> RJ-45	URL filtering System event log DMZ support Network address translation (NAT)	√ √ √
Wireless LAN features		NAT functionality	PPTP, L2TP, IPSec, RTSP, H.323, SIP, PPPoE
Wi-Fi band * Top Wi-Fi standard * WLAN data transfer rate (max) * Wi-Fi standards Modulation	Tri-band (2.4 GHz / 5 GHz / 5 GHz) Wi-Fi 6 (802.11ax) 6600 Mbit/s 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax) 1024-QAM	Protocols Universal Plug and Play (UPnP)  Design  Product colour On/off switch Product type *	White ✓ Tabletop router
Network		Antenna	. da.letep leate.
Ethernet LAN * Ethernet LAN interface type * Ethernet LAN data rates	✓ Gigabit Ethernet 1000 Mbit/s	Antenna design * Antennas quantity	Internal 6
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE	Features	
Port forwarding Dynamic DNS (DDNS) VPN support	802.11g, IEEE 802.11n  ✓ IPSec, PPTP, L2TP, PPTP, OpenVPN	Built-in processor Processor frequency Processor cores Internal memory Flash memory	1500 MHz 4 512 MB 256 MB
Mobile network		Power	
3G 4G	×	Power source type * AC input voltage	AC 110 - 240 V
Ports & interfaces Ethernet LAN (RJ-45) ports * USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A	3 🗸	AC input frequency Output voltage Output current	110 - 240 V 50 - 60 Hz 19 V 1.75 A
ports quantity	1	System requirements	
Memory card slot(s)	X	Windows operating systems supported	Windows 10, Windows 7, Windows 8
Management features Web-based management Quality of Service (QoS) support	<b>*</b>	Mac operating systems supported	Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion
Reset button	<b>V</b>	Weight & dimensions	
WPS push button	✓	Width	160 mm

Security		Weight & dimensions	
Security algorithms	WPA-Enterprise, WPA-PSK, WPA2- Enterprise, WPA2-PSK, WPS	Depth Height	75 mm 161.5 mm
Firewall Guest access	<b>√</b>	Weight	716 g
Stateful Packet Inspection (SPI)	ection (SPI)	Packaging data	
DoS attack prevention   ✓  Filtering	✓	Number of products included	2 pc(s)
	<b>✓</b>	Logistics data	
		Harmonized System (HS) code	85176990

