Viewsonic VX Series VX3276-2K-mhd-2 computer monitor 81.3 cm (32") 2560 x 1440 pixels Quad HD LED Silver

Brand : Viewsonic

Product family: VX Series

Product code: VX3276-2K-MHD-2

Product name : VX3276-2K-mhd-2

- SuperClear IPS panel for vivid picture quality and wider viewing angles
- Frameless bezel and stylish stand
- QHD (2560 x 1440) resolution for crisp, clear image detail
- Adaptive Sync delivers smooth, continuous visuals
- Flexible connectivity with DisplayPort, Mini DisplayPort and two HDMI ports

32" IPS QHD Entertainment Monitor, 2560 x 1440 px, 16:9, 250 cd/m², 4 ms, 75 Hz, 178°/178°, 2 x HDMI 1.4, DisplayPort, Mini DisplayPort

Viewsonic VX Series VX3276-2K-mhd-2. Display diagonal: 81.3 cm (32"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LED, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). VESA mounting. Product colour: Silver

Display

Display diagonal *	81.3 cm (32")
Display resolution *	2560 x 1440 pixels
HD type *	Quad HD
Native aspect ratio *	16:9
Display technology *	LED
Panel type *	IPS
Touchscreen *	✘
Display brightness (typical)	250 cd/m²
Response time *	4 ms
Anti-glare screen	✔
Screen shape *	Flat
Contrast ratio (typical) *	1200:1
Contrast ratio (dynamic)	80000000:1
Maximum refresh rate *	75 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	1.07 billion colours
Pixel pitch	0.273 x 0.273 mm
Digital horizontal frequency	15 - 113 kHz
Digital vertical frequency	24 - 75 Hz
Colour depth	10 bit
sRGB coverage (typical)	103%
NTSC coverage (typical)	72%

Performance

VESA Adaptive Sync support	✔
Flicker-free technology	✔
Low Blue Light technology	✔

Ports & interfaces

Headphone connectivity	3.5 mm
AC (power) in	✔

Ergonomics

VESA mounting *	✔
Panel mounting interface	100 x 100 mm
Cable lock slot *	✔
Cable lock slot type	Kensington
Tilt adjustment	✔
Tilt angle range	-4 - 15°

Power

Energy efficiency class (SDR) *	G
Energy consumption (SDR) per 1000 hours *	40 kWh
Power consumption (typical) *	43 W
Power consumption (standby) *	0.3 W
Power consumption (max)	46 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
European Product Registry for Energy Labelling (EPREL) code	407460

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 90%

Weight & dimensions

Width (with stand)	713 mm
Depth (with stand)	230 mm
Height (with stand)	504 mm
Weight (with stand)	6.2 kg

Multimedia

Number of speakers	2
RMS rated power	4 W
Built-in speaker(s) *	✔

Design

Market positioning *	Home
Product colour *	Silver
Feet colour	Silver

Ports & interfaces

HDMI *	✔
HDMI ports quantity	2
HDMI version	1.4
DisplayPorts quantity	1
Mini DisplayPorts quantity	1
Headphone out *	✔
Headphone outputs	1

Weight & dimensions

Width (without stand)	713 mm
Depth (without stand)	38 mm
Height (without stand)	416 mm
Weight (without stand)	5.6 kg

Packaging data

Package width	806 mm
Package depth	109 mm
Package height	509 mm
Package weight	8.2 kg

Packaging content

Cables included	AC, HDMI
Quick start guide	✔

Logistics data

Harmonized System (HS) code	85285210

0766907002959

766907002959

Publication date: 04-NOV-2024. Prints or copies of Information are only valid on the printed Publication date