

Philips S Line 243S1/00 computer monitor 60.5 cm (23.8") 1920 x 1080 pixels Full HD LCD Black

Brand : Philips

Product family: S Line

Product code: 243S1/00

Product name : 243S1/00

Business Monitor 243S1 LCD monitor with USB-C docking

Philips S Line 243S1/00 computer monitor 60.5 cm (23.8") 1920 x 1080 pixels Full HD LCD Black:

The Philips USB-C monitor replaces cable clutter. View FHD image and recharge a laptop, all at the same time with a single USB-C cable. Features like Daisy chain for multi-display setup, Eye comfort with TUV certified to reduce eye fatigue

Philips S Line 243S1/00. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Display surface: Matt, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 2 (3.1 Gen 2). VESA mounting, Height adjustment. Product colour: Black







| Display | | Ergonomics | |
|--|-----------------------|--|--|
| Display diagonal * | 60.5 cm (23.8") | Pivot angle | -90 - 90° |
| Display resolution * | 1920 x 1080 pixels | Swivelling | 4 |
| HD type * | Full HD | Swivel angle range | -180 - 180° |
| Native aspect ratio * | 16:9 | Tilt angle range | -5 - 25° |
| Display technology * | LCD | On Screen Display (OSD) | 4 |
| Panel type * | IPS | | Simplified Chinese, Traditional |
| Backlight type | W-LED | | Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, |
| Touchscreen * | × | On Screen Display (OSD) languages | Greek, Hungarian, Italian, Japanese, |
| Display brightness (typical) | 300 cd/m ² | | Korean, Polish, Portuguese, Russian, |
| Response time * | 4 ms | | Swedish, Turkish, Ukrainian |
| Display surface | Matt | Number of OSD languages | 21 |
| Anti-glare screen | 1 | Plug and Play | V |
| Screen shape * | Flat | LED indicators | Operation, Stand-by |
| Aspect ratio | 16:9 | Power | |
| Contrast ratio (typical) * | 1000:1 | Energy efficiency class (SDR) * | D |
| Contrast ratio (dynamic) | 5000000:1 | Energy efficiency class (HDR) * | Not available |
| Dynamic contrast ratio marketing name | SmartContrast | Energy consumption (SDR) per 1000 hours * | ⁾ 14 kWh |
| Maximum refresh rate * | 75 Hz | Power consumption (typical) * | 14 W |
| Viewing angle, horizontal | 178° | Power consumption (standby) * | 0.3 W |
| Viewing angle, vertical | 178° | Power consumption (off) | 0.3 W |
| Display number of colours * | 16.7 million colours | Power consumption (PowerSave) | 12.9 W |
| Pixel pitch | 0.2745 x 0.2745 mm | AC input voltage | 100 - 240 V |
| Pixel density | 93 ppi | AC input frequency | 50 - 60 Hz |
| Horizontal scan range | 30 - 85 kHz | Power supply type | Internal |
| Vertical scan range | 48 - 75 Hz | Energy efficiency scale | A to G |
| Viewable size, horizontal | 52.7 cm | European Product Registry for Energy Labelling (EPREL) code | 1014111 |
| Viewable size, vertical | 29.6 cm | | |
| Display diagonal (metric) | 60.5 cm | | |
| DDC/CI | 1 | | |

| Display | | One we tie we have a state of the second sec | |
|--|---------------------------------|--|---|
| Display | | Operational conditions | |
| Haze rate | 25% | Operating temperature (T-T) | 0 - 40 °C |
| Surface hardness | 3H | Storage temperature (T-T) | -20 - 60 °C |
| Colour gamut standard | sRGB | Operating relative humidity (H-H) | 20 - 80% |
| sRGB coverage (typical) | 107% | Operating altitude | 0 - 3658 m |
| NTSC coverage (typical) Display sRGB | 91% ✓ | Non-operating altitude | 3658 - 12192 m |
| | v | Weight & dimensions | |
| Performance | | Width (with stand) | 540 mm |
| NVIDIA G-SYNC * | × | Depth (with stand) | 205 mm |
| AMD FreeSync * | × | Height (with stand) | 482 mm |
| Fast charging | | Weight (with stand) | 5.28 kg 540 mm |
| Fast charging technology Component video sync | Power Delivery Separate sync | Width (without stand) Depth (without stand) | 540 mm |
| Flicker-free technology | | Height (without stand) | 323 mm |
| Low Blue Light technology | | Weight (without stand) | 3.42 kg |
| Multimedia | • | | |
| | 2 | Packaging data | 625 |
| Number of speakers RMS rated power | 2 4 W | Package width Package depth | 625 mm 180 mm |
| Built-in speaker(s) * | 4 00 | Package height | 435 mm |
| Built-in camera * | × | Package weight | 8.46 kg |
| | ~ | | 0.+0 kg |
| Design | | Packaging content | |
| Market positioning * | Office | Stand included | |
| Product colour * Front bezel colour | Black Black | Cables included Manual | HDMI, DisplayPort, USB Type-C, AC |
| Feet colour | Black | Bundled software | SmartControl |
| | DIACK | | Smarcontrol |
| Ports & interfaces | | Sustainability | |
| Built-in USB hub * | | Sustainability compliance | |
| USB hub version | 3.2 Gen 2 (3.1 Gen 2) | Sustainability certificates Doesn't contain | ENERGY STAR, TCO |
| USB upstream port type Number of upstream ports | USB Type-C 1 | | PVC/BFR, Mercury |
| USB Type-A downstream ports | | Other features | |
| quantity | 4 | Compatible operating systems | Mac OS X Windows 10 / 8.1 / 8 / 7 |
| USB Type-C DisplayPort Alternate | 1 | USB Power Delivery revision | 3.0 |
| Mode | | Exterior finish type Picture enhancement | Textured |
| USB Power Delivery USB Power Delivery up to | ✓ 65 W | Recyclable packaging material | SmartImage 100% |
| HDMI * | | | CB; FCC Class B; ICES-003; CE Mark; |
| HDMI ports quantity HDMI version | 1 1.4 | Regulatory Approvals | TUV/GS; TUV Ergo; CU-EAC; EAEU RoHS; TUV Eye Comfort certified |
| DisplayPorts quantity | 1.4 | Heavy metals free | Hg (mercury) |
| DisplayPort version | 1.2 | EasyRead mode | 4 |
| Audio output | 1 | LowBlue mode | 4 |
| HDCP | 1 | Energy efficiency class (old) | D |
| HDCP version | 1.4 | Compliance certificates | RoHS |
| DisplayPort output | 1 | Mean time between failures (MTBF) | 70000 h |
| Network | | Ethernet LAN data rates Wake-on-LAN | 10,100,1000 Mbit/s |
| Ethernet LAN | 1 | | CB, FCC Class B, ICES-003, CE Mark, |
| Ergonomics | | Certification | TUV/GS, TUV Ergo, SEMKO, CU-EAC, EAEU RoHS, TUV Eye Comfort |
| VESA mounting * | < | | certified |
| Panel mounting interface | 100 x 100 mm | Recycling data | |
| Cable lock slot * | ✓ | Post-consumer recycled plastic | 85% |
| Cable lock slot type | Kensington | Logistics data | |
| Height adjustment * | √ | Harmonized System (HS) code | 85285210 |
| Height adjustment | 13 cm | | 55205210 |
| Pivot | ✓ | | |





8712581784744

0609585254886



609585254886

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.