

Manhattan HDMI Cable with Ethernet, 4K@60Hz (Premium High Speed), 2m, Male to Male, Black, Equivalent to HDMM2MP, Ultra HD 4k x 2k, Fully Shielded, Gold Plated Contacts, Lifetime Warranty, Polybag



Brand : Manhattan Product code: 355735

Product name : HDMI Cable with Ethernet, 4K@60Hz (Premium High Speed), 2m, Male to Male, Black, Equivalent to HDMM2MP, Ultra HD 4k x 2k, Fully Shielded, Gold Plated Contacts, Lifetime Warranty, Polybag

- Premium certified HDMI cable
- Supports 4K@60Hz Ultra High Definition (UHD) resolution, 3D video and Deep Color
- Supports 4:4:4 Chroma Subsampling and HDR
- Gold-plated contacts for corrosion-free connections
- Up to 18 Gbps bandwidth
- Supports HDMI Ethernet Channel (HEC)
- High-speed Ethernet, bi-directional networking up to 100 Mbps
- Supports HDMI Audio Return Channel (ARC)
- ARC to transmit TV's audio through your system; no need for additional cable
- Compliant with Premium High Speed HDMI with Ethernet specifications
- Double shielded to reduce EMI and other interference sources
- Compatible with any HDMI device, such as a Blu-ray player, game console, stereo, PC and more
- Lifetime warranty

HDMI Cable with Ethernet, 4K@60Hz (Premium High Speed), 2m, Male to Male, Black, Equivalent to Startech HDMM2MP, Ultra HD $4k \times 2k$, Fully Shielded, Gold Plated Contacts, Lifetime Warranty, Polybag

Features		Features	
Cable length * Connector 1 * Connector 2 * Connector 1 gender * Connector 2 gender * Connector 1 form factor Connector 2 form factor Product colour * Supported graphics resolutions Supported video modes	2 m HDMI Type A (Standard) HDMI Type A (Standard) Female Female Straight Straight Black 3840 x 2160 1080p, 1440p	High Dynamic Range (HDR) supported Bandwidth Maximum refresh rate AWG wire size Connector contacts plating * Cable jacket material Magnetically shielded Certification Quantity per pack *	 ✓ 600 MHz 60 Hz 30 Gold Polyvinyl chloride (PVC) ✓ ISO 9002 1 pc(s)
Dolby technologies Audio Return Channel (ARC) HDMI Ethernet channel Data transfer rate	Dolby Vision, Dolby Atmos 18 Gbit/s	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C -20 - 60 °C 0 - 96%





766623355735

0766623355735

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.