

**Philips 75BDL4511D/00 Signage Display Digital A-board 190.5 cm (75") 500 cd/m<sup>2</sup> 4K Ultra HD Black 24/7**

**Brand :** Philips

**Product code:** 75BDL4511D/00

**Product name :** 75BDL4511D/00


75" 4K UHD 3840 x 2160 ADS, 500cd/m<sup>2</sup>, 1.07 Billion, 16:9, Response 8ms, DisplayPort, DVI-I, HDMI, USB, RJ45, RS232C, OPS, 24/7

Philips 75BDL4511D/00. Product design: Digital A-board. Display diagonal: 190.5 cm (75"), Display resolution: 3840 x 2160 pixels, Display brightness: 500 cd/m<sup>2</sup>, HD type: 4K Ultra HD. Operating hours (hours/days): 24/7. Product colour: Black



Display		Design	
Display diagonal *	190.5 cm (75")	VESA mounting *	✓
Display resolution *	3840 x 2160 pixels	Panel mounting interface	400 x 400 mm
Display brightness *	500 cd/m <sup>2</sup>	Bezel width (bottom)	1.49 cm
HD type *	4K Ultra HD	Bezel width (side)	1.49 cm
Touchscreen *	✗	Bezel width (top)	1.49 cm
Native aspect ratio	16:9	Mounting type	Wall
Response time	8 ms	Performance	
Contrast ratio (typical)	1200:1	Purpose *	Commercial
Contrast ratio (dynamic)	500000:1	On Screen Display (OSD)	✓
Viewing angle, horizontal	178°	On Screen Display (OSD) languages	Arabic, Simplified Chinese, Traditional Chinese, Danish, Dutch, English, Finnish, French, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Swedish, Turkish
Viewing angle, vertical	178°	Operating hours (hours/days)	24/7
Display number of colours	1.07 billion colours	Power	
Pixel pitch	0.4296 x 0.4296 mm	Power consumption (typical) *	185 W
Display diagonal (metric)	189.3 cm	Power consumption (standby) *	0.5 W
Panel life	50000 h	Energy efficiency class (SDR)	G
Haze rate	25%	Energy consumption (SDR) per 1000 hours	204 kWh
Ports & interfaces		AC input voltage	100 - 240 V
HDMI ports quantity *	4	AC input frequency	50 - 60 Hz
HDMI version	2.0	Energy efficiency scale	A to G
HDMI input ports quantity	3	Computer system	
HDMI output ports quantity	1	Video formats supported	H.263, H.264, H.265, MPEG
DVI port *	✓	Audio formats supported	AAC, HE-AAC
DVI-I ports quantity	1	Image formats supported	BMP, JPEG, PNG
DisplayPorts quantity *	2		
DisplayPorts in	1		
DisplayPorts out	1		
USB port *	✓		
USB ports quantity	2		
USB version	2.0		

Ports & interfaces		Weight & dimensions	
Ethernet LAN *	✓	Display width	1683.5 mm
Ethernet LAN (RJ-45) ports	1	Display depth	69.5 mm
Audio (L/R) in	1	Display height	961.7 mm
Audio (L/R) out	1	Display weight	35.9 kg
RS-232C	✓	Packaging content	
Remote (IR) input	1	Remote control included	✓
Remote (IR) output	1	Batteries included	✓
OPS module slot	✓	Cables included	AC, IR sensor, RS-232
Audio		Operational conditions	
Built-in speaker(s) *	✓	Operating temperature (T-T)	0 - 40 °C
Number of built-in speakers	2	Operating relative humidity (H-H)	20 - 80%
RMS rated power	20 W	Storage temperature (T-T)	-20 - 60 °C
Design		Storage relative humidity (H-H)	5 - 95%
Product design *	Digital A-board	Logistics data	
Placement supported *	Indoor	Harmonized System (HS) code	85285210
Orientation	Horizontal/Vertical	Technical details	
Product colour *	Black	Sustainability certificates	ENERGY STAR
		Compliance certificates	RoHS



8712581778682

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 04-NOV-2024. Prints or copies of Information are only valid on the printed Publication date