

DELL E Series 22 Inch Monitor - E2223HN

Brand: DELL **Product family:** E Series Product code: DELL-E2223HN

Product name: Dell 22 Inch

Monitor - E2223HN

- 54.5cm (21.45") Full HD 1920 x 1080 LED VA
- 10ms, 16:9, 250cd/m², 3000:1
- VGA, HDMI

54.5cm (21.45") Full HD 1920 x 1080 LED VA, 16:9, 250cd/m², 16.7M, 10ms, 178°/178°, 3000:1

DELL E Series 22 Inch Monitor - E2223HN:

Get outstanding value with this 21.5-inch FHD monitor featuring a wide viewing angle, HDMI, VGA connectivity and an eco-conscious design.

DELL E Series 22 Inch Monitor - E2223HN. Display diagonal: 54.5 cm (21.4"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 10 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. VESA mounting. Product colour: Black











Display		Power	
Display diagonal *	54.5 cm (21.4")	Energy efficiency class (SDR) *	D
Display resolution *	1920 x 1080 pixels	Energy efficiency class (HDR) *	Not available
HD type *	Full HD	Energy consumption (SDR) per 100	⁰ 12 kWh
Native aspect ratio *	16:9	hours *	
Display technology *	LCD	Power consumption (typical) *	12.83 W
Panel type *	VA	Power consumption (standby) *	0.3 W
Backlight type	LED	Power consumption (max)	19 W
Touchscreen *	×	Power consumption (off)	0.3 W
Display brightness (typical)	250 cd/m ²	AC input voltage	100 - 240 V
Response time *	10 ms	AC input frequency	50 - 60 Hz
Anti-glare screen	✓	Input current	0.7 A
Screen shape *	Flat	Power supply type	Internal
Contrast ratio (typical) *	3000:1	European Product Registry for	1031309
Maximum refresh rate *	60 Hz	Energy Labelling (EPREL) code	
Viewing angle, horizontal	178°	Operational conditions	
Viewing angle, vertical	178°	Operating temperature (T-T)	0 - 40 °C
Display number of colours *	16.7 million colours	Storage temperature (T-T)	-20 - 60 °C
Response time (fast)	5 ms	Operating relative humidity (H-H)	10 - 80%
Pixel pitch	0.249 x 0.241 mm	Storage relative humidity (H-H)	5 - 90%
Pixel density	103 ppi	Operating altitude	0 - 5000 m
Horizontal scan range	30 - 83 kHz	Non-operating altitude	5000 - 12192 m
Vertical scan range	50 - 75 Hz	Weight & dimensions	
Viewable size, horizontal	47.9 cm	Width (with stand)	504.3 mm
Viewable size, vertical	26 cm	Depth (with stand)	171 mm
Viewable size diagonal	54.5 cm	Height (with stand)	384.2 mm
Display diagonal (metric)	54.48 cm	Weight (with stand)	2.59 kg
High Dynamic Range (HDR) supported	×	Width (without stand)	504.3 mm
Colour gamut standard	DCI-P3	Depth (without stand)	49.6 mm
Colour gamut	83%	Height (without stand)	295.4 mm
Performance		Weight (without stand)	2.26 kg
		Bezel width (side)	1.28 cm
NVIDIA G-SYNC *	X	Bezel width (top)	1.28 cm
AMD FreeSync *	×	Bezel width (bottom)	1.69 cm

Multimedia		Packaging data	
Built-in speaker(s) * Built-in camera *	×	Package width Package depth	565.9 mm 355 mm
Design		Package height	119.8 mm
Market positioning *	Office	Package weight	4.14 kg
Product colour *	Black	Sustainability	
Front bezel colour	Black	Sustainability certificates	ENERGY STAR, TCO
Detachable stand	✓	Doesn't contain	PVC/BFR
Feet colour	Black	Carbon footprint	
Ports & interfaces		Total carbon footprint (kg of CO2e)	498
Built-in USB hub * VGA (D-Sub) ports quantity	X 1	Total carbon emissions, standard deviation (kg of CO2e)	121
HDMI * HDMI ports quantity	√ 1	Carbon emissions, manufacturing (kg of CO2e)	326
HDMI version	1.4	Carbon emissions, logistics (kg of CO2e)	35
Headphone out * AC (power) in	X ✓	Carbon emissions, energy usage (kg of CO2e)	133
Network		Carbon emissions, end-of-life (kg of CO2e)	2
Wi-Fi	×	Total carbon emissions, w/o use	362
Ergonomics		phase (kg of CO2e)	
VESA mounting *	✓	PAIA version	1.3.0
Panel mounting interface	100 x 100 mm	Other features	
Cable lock slot *	✓	Heavy metals free	Hg (mercury)
Cable lock slot type	Kensington	Compliance certificates	RoHS
Height adjustment *	×	Logistics data	
Pivot	X	Harmonized System (HS) code	85285210
Swivelling	×	•	
Tilt angle range	√		
Tilt angle range	-5 - 21°		
On Screen Display (OSD) Plug and Play	1		
LED indicators	Ž		
	•		



5397184505359

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.