PHILIPS

Philips B Line 276B1/75 LED display 68.6 cm (27") 2560 x 1440 pixels Full HD Black

Brand : Philips Product family: B Line Product code: 276B1/75

Product name: 276B1/75

Monitor 276B1 LCD monitor with USB-C docking

Philips B Line 276B1/75 LED display 68.6 cm (27") 2560 x 1440 pixels Full HD Black:

This Philips monitor offers 90W power delivery and a simple laptop docking solution. View QHD images, recharge a laptop and stay connected to Ethernet, all at the same time with a single USB-C cable. Eye comfort with TUV certification to reduce eye fatigue.

Philips B Line 276B1/75. Display diagonal: 68.6 cm (27"), Display resolution: 2560 x 1440 pixels, HD type: Full HD, Display technology: LED, Display surface: Matt, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 2.0 / 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black











| Display | | Ergonomics | |
|---|---|---|--|
| Display diagonal * Display resolution * HD type * | 68.6 cm (27") 2560 x 1440 pixels Full HD | VESA mounting * Panel mounting interface Cable lock slot * | √ 100 x 100 mm √ |
| Native aspect ratio * Display technology * Panel type * Backlight type Touchscreen * Display brightness (typical) Response time * Display surface Anti-glare screen Screen shape * Aspect ratio Contrast ratio (typical) * Contrast ratio (dynamic) | 16:9 LED IPS W-LED 350 cd/m² 4 ms Matt ✓ Flat 16:9 1000:1 50000000:1 | Cable lock slot type Height adjustment * Height adjustment Pivot Pivot angle Swivelling Swivel angle range Tilt adjustment Tilt angle range On Screen Display (OSD) | Kensington ✓ 15 cm ✓ -90 - 90° ✓ -180 - 180° ✓ 5 - 35° ✓ Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, |
| Dynamic contrast ratio marketing name Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical | SmartContrast 75 Hz 178° 178° | Number of OSD languages Plug and Play LED indicators | Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian 21 ✓ Operation, Stand-by |
| Display number of colours * | 16.7 million colours | Power | operation, stand 2, |
| Pixel pitch Pixel density Horizontal scan range Vertical scan range Viewable size, horizontal Viewable size, vertical Digital horizontal frequency Digital vertical frequency Display diagonal (metric) DDC/CI | 0.2331 x 0.2331 mm 109 ppi 30 - 114 kHz 48 - 75 Hz 59.7 cm 33.6 cm 30 - 114 kHz 48 - 75 Hz 68.6 cm ✓ | Energy efficiency class (SDR) * Energy consumption (SDR) per 1000 hours * Power consumption (typical) * Power consumption (standby) * Power consumption (PowerSave) AC input voltage AC input frequency AC adapter output voltage Power supply type | F 26 kWh 20.2 W 0.3 W 16.4 W 100 - 240 V 50 - 60 Hz 19 V |

| Display | | Power | |
|---|-----------------------------|--|---|
| Haze rate | 25% | Energy efficiency scale | A to G |
| Surface hardness | 3H | European Product Registry for Energy Labelling (EPREL) code | 349924 |
| Colour gamut standard Colour gamut | sRGB 110% | Operational conditions | |
| sRGB coverage (typical) | 107% | • | 0 - 40 °C |
| NTSC coverage (typical) | 104% | Operating temperature (T-T) Storage temperature (T-T) | -20 - 60 °C |
| Display sRGB | ✓ | Operating relative humidity (H-H) | 20 - 80% |
| Performance | | Operating altitude | 0 - 3658 m |
| NVIDIA G-SYNC * | × | Non-operating altitude | 0 - 12192 m |
| AMD FreeSync * | × | Weight & dimensions | |
| Component video sync | Separate sync | Width (with stand) | 613 mm |
| Flicker-free technology | ✓ | Depth (with stand) | 225 mm |
| Low Blue Light technology | ✓ | Height (with stand) | 537 mm |
| Multimedia | | Weight (with stand) | 7.26 kg |
| Number of speakers | 2 | Width (without stand) | 613 mm |
| RMS rated power | 4 W | Depth (without stand) | 54 mm |
| Built-in speaker(s) * | ✓ | Height (without stand) Weight (without stand) | 366 mm |
| Built-in camera * | × | | 5.47 kg |
| Design | | Packaging data | |
| Market positioning * | Business | Package width | 730 mm |
| Product colour * | Black | Package depth Package height | 193 mm 471 mm |
| Front bezel colour | Black | Package weight | 10.9 kg |
| Feet colour | Black | 3 3 | 10.5 Kg |
| Ports & interfaces | | Packaging content Stand included | 1 |
| Built-in USB hub * | V | Cables included | HDMI, DisplayPort, USB Type-C, AC |
| USB hub version | 2.0 / 3.2 Gen 1 (3.1 Gen 1) | Manual | J |
| USB upstream port type Number of upstream ports | USB Type-C 1 | Bundled software | SmartControl |
| Number of USB Type-C upstream | | Sustainability | |
| ports quantity | 1 | Sustainability certificates | ENERGY STAR, TCO |
| USB Type-A downstream ports quantity | 4 | Doesn't contain | Mercury, PVC/BFR |
| USB Type-C downstream ports | | Other features | |
| quantity | 1 | HBR3 support | 1 |
| USB Type-C DisplayPort Alternate Mode | ✓ | Exterior finish type | Textured |
| USB Power Delivery | √ | Picture enhancement | SmartImage |
| USB Power Delivery up to | 90 W | Recyclable packaging material | 100% |
| HDMI * | ✓ | | cETLus; CB; TUV/GS; TUV Ergo; |
| HDMI ports quantity | 2 | Regulatory Approvals | SEMKO; CU-EAC; EAEU RoHS; CE Mark; FCC Class B; ICES-003; |
| HDMI version | 1.4 | · · · · · · · · · · · · · · · · · · · | UKRAINIAN; TUV Eye Comfort |
| DisplayPorts quantity | 1 | Heavy metals free | certified; CCC; CECP; CEL Hg (mercury), Pb (lead) |
| DisplayPort version | 1.4 | Light sensor | √ (mercury), Fb (lead) |
| Audio output | √ | EasyRead mode | 1 |
| Headphone out * HDCP | × | LowBlue mode | ✓ |
| HDCP version | 1.4 | Compliance certificates | RoHS |
| AC (power) in | √ | Mean time between failures (MTBF) | 70000 h |
| DisplayPort output | ✓ | Wake-on-LAN | ✓ |
| Network | | | cETLus, CB, TUV/GS, TUV Ergo, SEMKO, CU-EAC, EAEU RoHS, CE |
| Ethernet LAN | ✓ | Certification | Mark, FCC Class B, ICES-003, |
| - | | | UKRAINIAN, TUV Eye Comfort certified, MEPS, RCM |
| | | Pocycling data | Co. aned, File of Nort |
| | | Recycling data | OE0/ |
| | | Post-consumer recycled plastic | 85% |





8712581774547

0609585253872



609585253872

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.