Logitech Rally Bar Mini

Brand : Logitech

Product code: 991-000389

Product name : Rally Bar Mini

Rally Bar Mini
Logitech Rally Bar Mini. HD type: 4K Ultra HD, Supported video modes: 576p, 720p, 900p, 1440p, 2160p, Maximum frame rate: 30 fps. Digital zoom: 4x. Ethernet LAN, Wi-Fi. Display: IPS, Display diagonal: 25.6 cm (10.1"), Display resolution: 1280 x 800 pixels. Product colour: Graphite

Performance

Product colour *	Graphite
Pan range	-25 - 25°
Tilt angle range	-15 - 15°
PTZ control	✔

Video

HD type *	4K Ultra HD
Supported video modes	576p, 720p, 900p, 1440p, 2160p
Maximum frame rate	30 fps

Audio

Built-in speaker(s)	✔
Output level	92/99 dB
Line-out impedance	4 Ω
Output voltage Total Harmonic Distortion (THD)	2%
Audio beamforming	✔
Noise reduction	✔
Echo cancellation	✔
RMS rated power	5 W
Microphone pick-up range	4.5 m
Sample rates	0 - 48 kHz

Ports & interfaces

HDMI ports quantity	3
HDMI output ports quantity	2
HDMI input ports quantity	1
USB connector type	USB Type-A, USB Type-C
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3
Ethernet LAN (RJ-45) ports	1
DC-in jack	✔
Microphone in	✔

Interface module

Interface module RJ-45 ports quantity	1

Network

Ethernet LAN *	✔
Ethernet LAN data rates	10,100,1000 Mbit/s
Wi-Fi	✔
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
Supported network protocols	IPv4, IPv6
Security algorithms	128-bit AES

Camera

Zoom capability	✔
Digital zoom	4x

Microphone

Microphone frequency	90 - 16000 Hz
Microphone direction type	Omnidirectional
Sound pressure level (max)	90 dB
Number of microphones	6

Features

Telepresence *	✘
Motion sensor	✔
Cable lock slot	✔
Cable lock slot type	Kensington

Logistics data

Master (outer) case gross weight	8.87 kg
Master (outer) case length	808 mm
Master (outer) case width	258 mm
Master (outer) case height	302 mm
Harmonized System (HS) code	85176990

Battery

Battery capacity	0.675 Wh

Computer system

Windows operating systems supported	Windows 10, Windows 11
Mac operating systems supported	Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 95%
Storage temperature (T-T)	-40 - 70 °C
Heat dissipation	64 BTU/h

Power

Power source type	AC
AC input voltage	100 - 240 V
Current	4.754 A
DC input voltage	19 V
Battery technology	Lithium
Battery capacity	220 mAh
Number of batteries supported	2
Power plug type	Type G

Weight & dimensions

Interface module dimensions (W x D x H)	246.2 x 171.3 x 56.1 mm
Interface module weight	1 kg
Width	719 mm
Depth	101 mm
Height	91.4 mm
Weight	4.03 kg

Camera

Horizontal field of view	113°
Vertical field of view	80.7°
Diagonal field of view	120°
Remote control interface	Bluetooth

Display

Display	IPS
Display diagonal	25.6 cm (10.1")
Display resolution	1280 x 800 pixels
Contrast ratio (typical)	1000:1
Touchscreen	✓
Touchscreen type	Capacitive
Viewing angle, horizontal	85°
Viewing angle, vertical	85°
Display brightness	400 cd/m²
Oleophobic coating	✓

Microphone

Microphone sensitivity	-36 dB

Weight & dimensions

Package width	252 mm
Package depth	802 mm
Package height	289 mm
Package weight	8.87 kg

Packaging content

Cables included	AC, DC, HDMI, USB Type-A to USB Type-C
Power cable length	2.5 m
HDMI cable length	2 m
AC adapter included	✓
Mounting kit	✓
Remote control included	✓
Camera included	✓
Quick start guide	✓

5099206102149