. . ..

Canon i-SENSYS MF754Cdw Laser A4 1200 x 1200 DPI 33 ppm Wi-Fi

Brand : Canon

Product family: i-SENSYS

Product code: 5455C020

Product name : MF754Cdw

Print, copy, Scan, Fax, 33ppm, A4, 1024MB, LAN, USB, WiFi, LCD

Canon i-SENSYS MF754Cdw Laser A4 1200 x 1200 DPI 33 ppm Wi-Fi:

Streamline your everyday business tasks with the Canon i-SENSYS MF754Cdw. This colour multi-function laser printer with advanced connectivity facilitates collaboration in the cloud, with access to Google Drive, DropBox and OneDrive. Expedite job timelines with fast print and scan speeds, plus copy and fax capabilities, as well as simplified user experience from the customisable display.

Canon i-SENSYS MF754Cdw. Print technology: Laser, Printing: Colour printing, Maximum resolution: 1200 x 1200 DPI. Copying: Colour copying, Maximum copy resolution: 600 x 600 DPI. Scanning: Colour scanning, Optical scanning resolution: 600 x 600 DPI. Faxing: Colour faxing. Duplex functions: Scan. Maximum ISO A-series paper size: A4. Wi-Fi. Product colour: White






Printing		Paper handling	
Printing * Maximum resolution * Print speed (black, normal quality, A4/US Letter) * Warm-up time Time to first page (black, normal)	Laser Colour printing 1200 x 1200 DPI 33 ppm 14 s 7.1 s 7.1 s	ISO B-series sizes (B0B9) Non-ISO print media sizes Envelopes sizes Paper tray media weight	B5 Executive, Letter, Statement C5, Com-10, DL, Monarch 60 - 200 g/m ²
		Ports & interfaces	
		USB port USB 2.0 ports quantity	✓ 1
Copying		Network	
Duplex copying * Copying * Maximum copy resolution * Maximum number of copies Copier resize ID-card copy function	 Colour copying 600 x 600 DPI 999 copies 25 - 400% 	Wi-Fi * Ethernet LAN * Ethernet LAN data rates Wi-Fi standards Security algorithms	 10,100,1000 Mbit/s 802.11b, 802.11g, Wi-Fi 4 (802.11n) 64-bit WEP, 128-bit WEP, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPA2-TKIP
Scanning		Management protocols	SNMPv1, SNMPv3 (IPv4,IPv6)
Duplex scanning * Scanning * Optical scanning resolution * Scanner type * Scan to Input colour depth	Colour scanning 600 x 600 DPI ADF scanner Cloud, E-mail, FTP, USB 24 bit	Performance Internal memory * Built-in processor Processor frequency Sound power level (printing) Sound power level (standby)	1024 MB ✓ 1200 MHz 65 dB 41 dB
Output colour depth Greyscale levels	24 bit	Design	
Scan drivers	256 ICA, TWAIN, WIA	Product colour * Market positioning *	White Business
Fax		Built-in display *	 ✓
Faxing * Modem speed Fax memory Speed dialling	Colour faxing 33.6 Kbit/s 512 pages	Display Control type Colour display	LCD Touch ✔
Speed dialing	¥	Power	
		Power consumption (max)	1380 W

_

Features		Power	
Recommended duty cycle	750 - 4000 pages per month	Power consumption (printing)	700 W
Maximum duty cycle *	50000 pages per month	Power consumption (standby)	24 W
Duplex functions *	Scan	Power consumption (sleep)	1 W
Printing colours *	Black, Cyan, Magenta, Yellow	Energy Star Typical Electricity Consumption (TEC)	0.3 kWh/week
Input & output capacity		AC input voltage	220 - 240 V
Total number of input trays * Total input capacity * Total output capacity * Multi-Purpose tray	1 250 sheets 150 sheets ✓ 50 sheets	AC input frequency	50/60 Hz
		System requirements	
		Windows operating systems supported Mac operating systems supported	Windows 10, Windows 11, Windows 8.1
Multi-Purpose tray input capacity Auto document feeder (ADF)	Su sheets		Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.2 Jaguar, Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac
Auto document feeder (ADF) input			
capacity	50 sheets		
Maximum input capacity	850 sheets		
Paper handling			
Maximum ISO A-series paper size *	Α4		
	Coated paper, Envelopes, Heavy		OS X 10.9 Mavericks, Mac OS X 11.0
Paper tray media types *	paper, Plain paper, Postcard, Recycled paper, Thin paper		Big Sur, Mac OS X 12.0 Monterey
		Linux operating systems supported	4
ISO A-series sizes (A0A9) *	A4, A5, A6		Windows Server 2012, Windows
		Server operating systems supported	Server 2012 R2, Windows Server 2016, Windows Server 2019, Windows Server 2022
		Operational conditions	
		Operating relative humidity (H-H)	20 - 80%
		Operating temperature (T-T)	10 - 30 °C
		Weight & dimensions	

Weight & dimensions

Width	425 mm
Depth	461 mm
Height	430 mm
Weight	23.3 kg



8714574670928

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.