



# Lindy DST-Mini USB-C Laptop Mini Docking Station with 4K Support and 100W Pass-Through Charging

**Brand :** Lindy

**Product code:** 43358

**Product name :** DST-Mini USB-C Laptop Mini Docking Station with 4K Support and 100W Pass-Through Charging

- Adds two USB Type A ports, an HDMI port, Gigabit Ethernet and a Power Delivery port to your notebook
- Supports 4K 3840x2160 60Hz for an HDMI display
- Features DisplayPort Alternate Mode
- USB Power Delivery PD 3.0 capable up to 100W
- 2 year warranty

DST-Mini USB-C Laptop Mini Docking Station with 4K Support and 100W Pass-Through Charging  
 Lindy DST-Mini USB-C Laptop Mini Docking Station with 4K Support and 100W Pass-Through Charging.  
 Connectivity technology: Wired, Host interface: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, USB Power Delivery up to: 100 W. Ethernet LAN data rates: 10,1000 Mbit/s. Product colour: Black, Compatible memory cards: MicroSD (TransFlash), SD, Maximum digital resolution: 3840 x 2160 pixels. Width: 115 mm, Depth: 43 mm, Height: 12 mm. Quantity per pack: 1 pc(s), Package width: 174 mm, Package depth: 194 mm



Ports & interfaces		Performance	
Connectivity technology *	Wired	Product colour *	Black
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C	Plug and Play	✓
USB 2.0 ports quantity *	2	Charging function	✓
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	1	Housing material	Aluminium
USB Power Delivery	✓	Certification	CE, FCC, REACH & RoHS, CP65
USB Power Delivery revision	3.0	<b>Operational conditions</b>	
USB Power Delivery up to	100 W	Operating temperature (T-T)	0 - 55 °C
HDMI ports quantity *	1	Storage temperature (T-T)	-10 - 70 °C
HDMI version	2.0	Operating relative humidity (H-H)	10 - 85%
Microphone in *	✗	Storage relative humidity (H-H)	10 - 85%
HDCP	✓	<b>Weight &amp; dimensions</b>	
HDCP version	1.4/2.3	Width	115 mm
<b>Network</b>		Depth	43 mm
Ethernet LAN *	✓	Height	12 mm
Ethernet LAN (RJ-45) ports	1	Weight	74 g
Ethernet LAN data rates	10,1000 Mbit/s	<b>Packaging data</b>	
<b>Performance</b>		Quantity per pack	1 pc(s)
Card reader integrated *	✓	Package width	174 mm
Compatible memory cards	MicroSD (TransFlash), SD	Package depth	194 mm
Maximum digital resolution	3840 x 2160 pixels	Package weight	100 g
Maximum analog resolution	3840 x 2160 pixels	<b>Packaging content</b>	
Maximum refresh rate	60 Hz	Manual	✓



4002888433587

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 04-NOV-2024. Prints or copies of Information are only valid on the printed Publication date