



CERTIFICATE OF DROP TEST

Number : D120616

PRODUCT : Phoenix Fire Resistance Safe

PRODUCT INFORMATION : See attached table

PERFORMANCE SPECIFICATION : We guarantee that all models of fire safe was drop tested(9.1m) in our testing equipment in compliance with KS G 4500.

VALIDITY : This certificate is valid until June 15, 2017.

Busan Korea, June 16, 2012

A handwritten signature in black ink, appearing to read "Bongsoo Han".

Bongsoo Han / QC Manager

A handwritten signature in black ink, appearing to read "Younghoon Jung".

Younghoon Jung / President



CERTIFICATE OF DROP TEST

Number: D120616

PRODUCT: Phoenix Fire Resistance Safe

PERFORMANCE SPECIFICATION: We guarantee that all the models stated on the products information table have been drop tested (9.1m) in compliance with KS G 4500.

VALIDITY: This certificate is valid until June 15, 2017.

Product Information

| Model | External dimension (mm) | | | Internal dimension (mm) | | | Capacity (ℓ) | Weight (kg) |
|------------------------|-------------------------|-------|-------|-------------------------|-------|-------|--------------|-------------|
| | height | width | depth | height | width | depth | | |
| phoenix | | | | | | | | |
| FS1271E | 300 | 410 | 342 | 220 | 330 | 225 | 16 | 26 |
| FS1272E, DS2001 | 412 | 352 | 433 | 320 | 260 | 304 | 25 | 36 |
| FS1273 | 514 | 404 | 440 | 410 | 300 | 300 | 36 | 53 |
| DS2002 | 600 | 470 | 470 | 480 | 350 | 300 | 50 | 80 |
| DS2501 | 635 | 500 | 500 | 515 | 380 | 330 | 64 | 90 |
| DS2502 | 816 | 520 | 520 | 676 | 380 | 330 | 84 | 122 |
| DS2003 | 770 | 690 | 720 | 590 | 510 | 510 | 153 | 203 |
| SS1621 | 960 | 655 | 560 | 780 | 475 | 350 | 129 | 201 |
| DS2503 | 1060 | 655 | 560 | 880 | 475 | 350 | 146 | 209 |
| FS1901, SS1622, DS4621 | 1160 | 655 | 560 | 980 | 475 | 350 | 162 | 228 |
| SS1623 | 1385 | 775 | 650 | 1205 | 595 | 440 | 315 | 348 |
| FS1902, DS4622 | 1630 | 775 | 650 | 1450 | 595 | 440 | 379 | 388 |
| FS1903, DS4623 | 1685 | 1126 | 700 | 1505 | 946 | 490 | 698 | 540 |
| FS2242, FS2252K/E | 722 | 528 | 675 | 272 | 384 | 505 | 52 | 145 |
| FS2244, FS2254K/E | 1406 | 528 | 675 | 272 | 384 | 505 | 52 | 266 |
| FS2412 | 730 | 985 | 600 | 266 | 832 | 384 | 84 | 232 |
| FS2414 | 1390 | 985 | 600 | 266 | 832 | 384 | 84 | 392 |

* Outside dimension doesn't include the height of plastic feet or plinth.

Busan Korea, June 16, 2012

Bongsoo Han / QC Manager

Younghoon Jung / President