

HP Bright White Inkjet Paper



This specially treated paper delivers smooth lines and text, uniform fills and high-contrast colour and is perfect for everyday black and colour line drawings.

- Dries instantly and therefore ensures maximum productivity.
- Provides an economically priced, multipurpose paper that is perfect for everyday applications.
- Offers choice of roll lengths including 91m for reliable, trouble-free unattended printing.
- Available in true A1 and A0 size – to increase the productivity in the workflow – no trimming or cutting time wasted anymore before folding or framing.

This economical paper is designed for print service providers, engineers (CAD), architects (AEC) and Geographical Information System (GIS) users for applications such as check plots, posters, POP and retail displays as well as everyday presentations.

HP Bright White Inkjet Paper

Compatibility

HP Designjet printers	HP Ink supplies	Front panel setting
HP Designjet 5500/5000 Printer series	HP 81 Dye Ink Supplies	Bright White Inkjet Paper
HP Designjet 4000 Printer series	HP 90 Dye Ink Supplies	Bright White Inkjet Paper
HP Designjet 3000CP/2000CP Printer series	HP CP Dye Ink Supplies	Coated Paper
HP Designjet 1000 Printer series	HP 80 Dye Ink Supplies	Bright White Inkjet Paper
HP Designjet 800/500 Printer series	HP 10, 11 & 82 Dye Ink Supplies	Bright White Inkjet Paper
HP Designjet 700/750/755 Printer series	HP 45 Black/HP 44 CMY Dye Ink Supplies	Opaque Bond
HP Designjet 650/600 Printer series	HP 40 Black/HP 50 CMY/HP 26 Black Dye Ink Supplies	Opaque Bond
HP Designjet 400/300 Printer series	HP 40 Black, HP 44 CMY Dye Ink Supplies	Plain Paper
HP Designjet 130 Printer series*	HP 84, 85 Dye Ink Supplies	
HP Designjet 120/120NR Printer series*	HP 11, 82 & 84 Dye Ink Supplies	

For the latest ICC/Media profiles, please visit www.hp.com/go/designjet/supplies/support (click on the ICC profiles and select your printer). For non-Post Script printers see your external RIP Vendor.

Weight	90 g/m ² per ISO 536 Test Method
Thickness	4.8 mil/122 microns per ISO 534 Test Method
Opacity	93% per TAPPI T-425 Test Method
Brightness	95% per TAPPI T-452 Test Method
CIE whiteness	163 per CIE Ganz 82 Test Method
Lamination	Can be laminated with commercially available pressure-sensitive lamination films. For further information refer to our list of lamination partners at www.hp.com/go/designjet/supplies
Finish	Matte
Operating temperature	15° - 35 °C
Operating humidity	20% - 70% RH
Lightfastness (indoor)**	6 months (Dye)
Waterfastness	Lamination required
Dry time	90 seconds (@23 °C, 50% RH)
Shelf time	2 years, unopened in original packaging
Country of origin	Austria

Ordering information	Product Numbers	Roll sizes	UPC codes
	C6035A	610 mm x 45.7 m	0 88698-17176 9
	C6036A	914 mm x 45.7 m	0 88698-52306 3
	C6810A ¹	914 mm x 91 m	0 88698-59130 7
	Q1444A	(A0)/841 mm x 45.7 m	7 25184-99491 0
	Q1445A	(A1)/594 mm x 45.7 m	7 25184-99492 0

* Compatible with A1 and 24" rolls

** Information provided by Hewlett Packard. Tested on HP Designjet 5500/5000 Printer series with HP Dye Ink Supplies

¹ Compatible with HP Designjet 5500/5000, 4000 and 1000 Printer series only

Warranty Large Format Media HP Large Format Printing material is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. If for any reason the user is unsatisfied with HP Large Format Printing materials they should contact their HP reseller.

© 2005 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For information on similar products, please visit HP Designjet Supplies at www.hp.com/go/designjet/supplies

5982-9320EEE. January 2005

