

### Technical Specifications

#### HP USB Keyboard and Mouse Healthcare Edition



#### Models

HP USB Keyboard and Mouse Healthcare Edition

1VD81AA

#### Compatibility

The HP USB Keyboard and Mouse Healthcare Edition is compatible with HP ProDesk 400 G4 SFF, HP ProDesk 400 G4 MT, HP ProDesk 400 G3 DM (Mini), HP ProOne 400 G3 AIO Touch, HP ProOne 400 G3 AIO Non-Touch, HP ProDesk 600 G3 MT, HP ProDesk 600 G3 SFF, HP ProDesk 600 G3 Desktop Mini, HP ProOne 600 G3 AIO 21.5" Non-Touch, HP EliteDesk 800 G3 TWR, HP EliteDesk 800 G3 SFF, HP EliteDesk 800 G3 35W Desktop Mini, and HP EliteDesk 800 G3 65W Desktop Mini. HP EliteOne 800 G3 AIO 23.8" NT, HP EliteOne 800 G3 AIO 23.8" Touch, HP EliteOne 800 G3 AIO 23.8" Touch 4K.

*NOTE: Not all models are available in all regions.*

#### Service and Support

Your Option Limited Warranty is a one (1) year (HP Option Limited Warranty Period) parts replacement warranty on any HP-branded or Compaq-branded options (HP Options). If your HP Option is installed in an HP Hardware Product, HP may provide warranty service either for the HP Option Limited Warranty Period or the remaining Limited Warranty Period of the HP Hardware Product in which the HP Option is being installed, whichever period is the longer but not to exceed three (3) years from the date you purchased the HP Option.

### Technical Specifications

| Keyboard                 |  |  |
|--------------------------|--|--|
| Physical Characteristics | Keys   | 99 (US) 100(UK)                                      |
|                          | Dimensions (H x W x D)   | 13.5x4.4x1.1 in (342.5x112.5x28.0 mm)                |
|                          | Weight   | 0.6 lbs without cable (270 g)                        |
| Electrical               | ESD  | +/- 4KV  |
|                          | Operating voltage  | + 4.75 to 5.25VDC                                    |
|                          | Power consumption  | 50-mA maximum  |
|                          | System interface   | USB Type A plug connector                            |
|                          | EMI - RFI  | Conforms to FCC rules for a Class B computing device |
|                          | Microsoft PC 99 - 2001   | Functionally compliant                               |
| Mechanical               | Keycaps  | Low-profile design                                   |
|                          | Switch actuation   | 55±10g nominal peak force with tactile feedback      |
|                          | Switch life  | 10 million keystrokes (Life tester)                  |
|                          | Switch type  | Membrane switch                                      |
|                          | Key-leveling mechanisms  | For all double-wide and greater-length keys          |
|                          | Cable length   | 6 ft (1.8 m)   |
|                          | Microsoft PC 99 - 2001   | Mechanically compliant                               |
| Environmental            | Acoustics  | <40-dBA maximum sound pressure level                 |
|                          | Operating temperature  | 32° to 122° F (0° to 50° C)                          |
|                          | Non-operating temperature  | 23° to 131° F (-5° to 55° C)                         |
| Approvals                | FCC, CE Mark, C-Tick, ICES-003, EN 55022, EN55024, EN55032, (NRTL will be available by the end of March) |  |

| Mouse                    |  |   |
|--------------------------|--|---|
| Physical characteristics | Buttons  | 3 buttons + a scroll wheel  |
|                          | Dimensions (L x W x H)   | 4.7×2.5×1.5 in (118.9x64.5x37.3 mm)   |
|                          | Weight   | 0.2 lbs (100 g)   |
| Electrical               | ESD  | +/- 4KV   |
|                          | Operating voltage  | + 4.75 to 5.25VDC   |
|                          | Power consumption  | 50-mA maximum   |
|                          | System interface   | USB Type A plug connector   |
|                          | EMI - RFI  | Conforms to FCC rules for a Class B computing device  |
|                          | Microsoft® PC 99 - 2001  | Functionally compliant  |
|                          | Switch actuation   | 100±50g nominal peak force with tactile feedback  |
|                          | Switch life  | 3 million   |
|                          | Switch type  | Mechanical switch   |
|                          | Cable length   | 6 ft (1.8 m)  |
|                          | Microsoft PC 99 - 2001   | Mechanically compliant  |
| Environmental            | Acoustics  | <40-dBA maximum sound pressure level  |
|                          | Operating temperature  | 32° to 104° F (0° to 40° C)   |
|                          | Non-operating temperature  | -40° to 140° F (-40° to 60° C)  |
|                          | Non-operating vibration  | Frequency : 55 HZ, amplitude: 0.10Grm, 30 min.  |
|                          | Drop (in box)  | Height : 76.2 cm, b. ground : 30mm iron plate, c. test one corner, 3 edges, 6 surfaces(one time for each) |
| Approvals                | FCC, CE Mark, C-Tick, ICES-003, EN 55022, EN55024, EN55032, (NRTL will be available by the end of March) |   |

*Technical Specifications*

|   |   |
|---|---|
| Country of Origin<br>(keyboard and mouse) | China   |
| Kit contents<br>(keyboard and mouse)      | Keyboard, Keyboard Drape, Mouse, Installation Guide |

## Technical Specifications

© Copyright 2018 HP Development Company, L.P. All rights reserved. The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

| Date of change: | Version History: | Description of change:              |
|-----------------|------------------|-------------------------------------|
| June 16, 2017   | From V1 to V2    | First version uploaded in Concentra |
| March 7, 2018   | From V1 to V2    | ESD +/- 4KV added                   |
| August 21, 2018 | From V2 to V3    | Picture added                       |
|                 |                  |                                     |