# Key **Features**

Streamlined Desktop Display Solution | Enhanced Producitivity with Dual Monitor Setup | Reduce Clutter with Single-Cable Solution | A More Comfortable Workspace | Command and Control Made Easy



## Product **Description**


Designed to boost productivity and maximize output, the ViewSonic® VG2756-2K is a 27" QHD docking monitor that transforms your desktop into a streamlined and efficient workspace. Enjoy reliable and flexible network connectivity with the integrated gigabit Ethernet port, while the latest USB Type-C connectivity and Daisy Chain capability makes dual-monitor setup a breeze. That's not all, the integrated USB hub also provides single-cable simplicity for connecting and charging your peripherals and accessories. A best-in-class ergonomic design features 40-degree tilt and bi-directional pivot so your screen and workspace are as comfortable as you need. In addition, the included vDisplay software gives you quick and easy OSD control, as well as customized screen templates for easy multi-tasking. This monitor is also shipped in eco-friendly biodegradable packaging, along with an easy-to-install quick release stand that makes for quick deployment and a lower total cost of ownership.



- Menu Control Panel
  VESA Compatible Wall Mount (100 x 100 mm)
  VESA Compatible Client Mount (100 x 100 / 75 x 75 mm)
  AC In
- 02:10-03 0 04 : 05 -0-0.13 0E =
  - 11. USB Type-B 12. DisplayPort Out 13. USB Type-C







2560 x 1440 **RESOLUTION** 

## **c**all: 888.881.8781

- **Contact Sales** email: salesinfo@viewsonic.com
  - visit: viewsonic.com

Di	cn	la.	٧/٠
$\nu$	٦þ	ıa	у.

Display Size (in.):	27				
Viewable Area (in.):	27				
Panel Type:	IPS				
Resolution:	2560 x 1440				
Resolution Type:	QHD (2560x1440)				
Static Contrast Ratio:	1,000:1				
Dynamic Contrast Ratio:	50,000,000:1				
Light Source:	LED				
Brightness:	350 cd/m2				
Colors:	16.7M				
Color Space Support:	8 Bit				
Aspect Ratio:	16:9				
Response Time (Typical GTG):	14ms				
Response Time (GTG w/OD):	5ms				
Viewing Angles:	178º horizontal, 178º vertical				
Backlight Life (Hours):	30,000				
Panel Surface:	Anti-glare, Hard coating (3H)				
Compatibility:					
PC Resolution (max):	2560 x 1440				
Mac® Resolution (max):	2560 x 1440				
Connector:					
USB Type A(2), USB Type B(1), USB Type C(1), Ethernet LAN (RJ45)(1), HDMI 1.4 In(1), DisplayPort(1), DisplayPort Out(1)					
Audio:	Audio:				
Internal Speakers:	2W (x2)				
Power:					
Eco Mode (Conserve):	16.8				
Eco Mode (optimized):	21.2				
Consumption (typical):	30.7				
Consumption (max):	67.0				
Voltage:	AC 100-240V (universal), 50-60Hz				
Stand-by:	0.5W				
Power Supply:	Internal				
Additional Hardware:					
Kensington Lock Slot:	1				

Video	Si	ig	n	a	l	•
Freque	en	C١	/	Н		r

3		
Frequency Horizontal:	15 ~ 90 KHz	
Frequency Vertical:	49 ~ 75 Hz	
Video Input:		
Digital Sync:	TMDS for HDMI (v1.4), PCI-E for DisplayPort (v1.2), Micro-Packet for USB Type C	
Ergonomics:		
Height Adjust:	130 mm / 5.1 in	
Swivel:	120°	
Pivot (Right/Left):	90° / 90°	
Tilt (Forward/Back):	40° / 5°	
Weight (imperial):		
Net (lbs):	15.2	
Net Without Stand (lbs):	9.9	
Gross (lbs):	22.5	
Weight (metric):		
Net (kg):	6.9	
Net Without Stand (kg):	4.5	
Gross (kg):	10.2	
Dimensions (imperial) (WxHxD)	:	
Packaging (in.):	27.2 x 8.6 x 16.9	
Physical (in.):	24.1 x 16.0 x 8.0	
Physical Without Stand (in.):	24.1 x 14.3 x 2.0	
Dimensions (metric) (WxHxD):		
Packaging (mm):	692.0 x 218.0 x 430.0	
Physical (mm):	613.0 x 406.0 x 202.0	
Physical Without Stand (mm):	613.0 x 363.0 x 52.0	
General:		
Regulations: cTUVus, FCC-B, ICES003	3, Energy Star, EPEAT, MX-CoC, Mexico Energy	
PACKAGE CONTENTS: VG2756-2K, Power Cable, DP to DP Cable, USB Type Cable, USB Type B Uplink Cable, Quick Start Guide		
Recycle/Disposal: Please dispose of	in accordance with local, state or federal	

Warranty: Three-year limited warranty on parts, labor and backlight

Kensingtor	LOCK STOC.	'
Controls		

Physical Controls: 1,2,3,4,5,6 (Power)

> Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)

### **Operating Conditions:**

On Screen Display:

Temperature:	32-104° F (0 - 40° C)			
Humidity (non-condensing):	20-90%			
Mount:				
VESA Compatible:	100 x 100 mm			

UPC: 766907008548