ZYXEL

Zyxel GS1915-24E Managed L2 Gigabit Ethernet (10/100/1000) 1U Black

Brand : Zyxel **Product code:** GS1915-24E-GB0101F

Product name: GS1915-24E

- Supports Nebula to offer a unified cloud network experience, from wired, wireless to security gateway
- Nebula cloud management allows easy deployment, real-time configurations and effortless access to all your cloud devices anywhere, anytime
- Facilitate wide variety of network setups with flexible PoE budget of both 60 W (8EP) and 130 W (24EP) with all PoE ports supporting IEEE 802.3at PoE+
- Immediately check the Switch status by cloud indicator
- Compact and near-silent design is ideal for any working environment GS1915-24E, 24-port GbE Smart hybrid mode Switch, standalone or NebulaFlex Cloud, rackmount, fanless, GB





| Management features | | Multicast features | |
|---|---|-----------------------------------|------------------|
| Switch type * Switch layer | Managed L2 | Multicast support | ✓ |
| | | Protocols | |
| Quality of Service (QoS) support | √ | Management protocols | SNMP v1, v2c, v3 |
| Web-based management | √ | Design | |
| Cloud-managed MIB support | 1 | Rack mounting * | 1 |
| | • | Form factor | 10 |
| Ports & interfaces | | Product colour | Black |
| Basic switching RJ-45 Ethernet ports quantity * | 24 | LED indicators | 1 |
| Dania awitahina DI 45 Ethamat manta | Gigabit Ethernet (10/100/1000) | Wall mountable | ✓ |
| | | Performance | |
| Network | | Fanless | 1 |
| Networking standards * | IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, | Mean time between failures (MTBF) | 674068 h |
| | | Power | |
| 100 | IEEE 802.3x | Power source * | AC |
| 10G support * | × | Power supply included * | 1 |
| Port mirroring Flow control support | 1 | AC input voltage | 100 - 240 V |
| Broadcast storm control | 1 | AC input frequency | 50 - 60 Hz |
| Spanning tree protocol | , | Power consumption (max) | 15.5 W |
| Ethernet LAN data rates | 100,1000 Mbit/s | Power over Ethernet (PoE) | |
| VLAN support | √ | Power over Ethernet (PoE) * | × |
| Virtual LAN features | Port-based VLAN | Operational conditions | |
| Data transmission | | Operating temperature (T-T) | 0 - 40 °C |
| Switching capacity * | 48 Gbit/s | Storage temperature (T-T) | -40 - 70 °C |
| Forwarding rate | 35.7 Mpps | Operating relative humidity (H-H) | 10 - 95% |
| MAC address table * | 8000 entries | Heat dissipation | 53 BTU/h |
| Jumbo frames support | ✓ | Weight & dimensions | |
| Jumbo frames Packet buffer memory | 9000 525 MB | Width | 267 mm |
| | | Depth | 162 mm |
| | | Height | 42 mm |

| Security | | Weight & dimensions | |
|-------------------------------------|-------------------------|---------------------|---------|
| DHCP features | DHCP client, DHCP relay | Weight | 1.57 kg |
| IGMP snooping | / | Packaging data | |
| Security algorithms | | Package width | 325 mm |
| SSH/SSL support | | Package depth | 223 mm |
| Loop protection Password protection | Y | Package height | 71 mm |
| | √ | Package weight | 2.05 kg |



4718937626793

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.