NETGEAR WAX628 — Insight Managed WiFi 6 AX5400 Dual-band Multi-Gig PoE Access Point

Brand: NETGEAR Product code: WAX628-111EUS

Product name : WAX628 — Insight Managed WiFi 6 AX5400 Dual-band Multi-Gig PoE Access Point

- WiFi 6 dual-band 5.4Gbps
- WPA3 for highest level of WiFi connection security
- 4 years of ProSupport
- 4 years of Insight Pro

WAX628 WiFi 6 Access Point



WAX628 — Insight Managed WiFi 6 AX5400 Dual-band Multi-Gig PoE Access Point

4-years of ProSupport and 4-years of Insight Subscription are included

The WAX628 is a scalable solution for custom home installations of many sizes, delivering up to 5.4Gbps total WiFi throughput. Based on WiFi 6 technology, the WAX628 provides stable WiFi signals throughout every room of the house with low latency.

NETGEAR WAX628 — Insight Managed WiFi 6 AX5400 Dual-band Multi-Gig PoE Access Point. 2.4 GHz, 5 GHz. Security algorithms: EAP-TLS, PEAP, SSL/TLS, TTLS, WPA, WPA2, WPA3. Ethernet LAN data rates: 10,100,1000,2500 Mbit/s. Power over Ethernet (PoE). Product colour: White

Features		Management features	
2.4 GHz *	10,100,1000,2500 Mbit/s IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n 200 user(s) Multi User MIMO OFDM, OFDMA	Web-based management	✓
5 GHz *		Ports & interfaces	
Ethernet LAN data rates Networking standards		Ethernet LAN (RJ-45) ports * DC-in jack	1
•		Power	
Number of users Auto MDI/MDI-X MIMO MIMO type		Power over Ethernet (PoE) * Output voltage Output current	12 V 3.5 A
Spread spectrum method		Design	
	*	Placement * Product colour *	Ceiling, Wall White
Security		Reset button	✓
Security algorithms *	EAP-TLS, PEAP, SSL/TLS, TTLS, WPA, WPA2, WPA3	LED indicators Antenna	✓
MAC address filtering Service Set Identifier (SSID) features	SSID broadcast, SSID broadcast on/off	Antenna type * Antenna gain level (max)	Internal 4.4 dBi
Auto Wireless Distribution System (WDS)		Packaging content	
Remote Authentication Dial-In User Service (RADIUS)		Quantity per pack Mounting kit Quick start guide	1 pc(s) ✓
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C







606449163759

0606449163759

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.